

## Linear Systems PNP Transistor

The LS3550SC is a PNP transistor mounted in a TO-92 package.

The TO-92 provides ease of manufacturing.

(See Packaging Information).

### LS3550SC Features:

- Low Output Capacitance

### FEATURES

3 LEAD TO-92 PACKAGE

### ABSOLUTE MAXIMUM RATINGS<sup>1</sup>

@ 25°C (unless otherwise noted)

### Maximum Temperatures

Storage Temperature -65°C to +150°C

Operating Junction Temperature -55°C to +150°C

### Maximum Power Dissipation

Continuous Power Dissipation TBD

### Maximum Currents

Collector Current 10mA

### Maximum Voltages

Collector to Collector Voltage 80V

### ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTICS	MIN.	TYP.	MAX.	UNITS	CONDITIONS
$V_{CB0}$	Collector to Base Voltage	-20	--	--	V	$I_C = 10\mu A, I_E = 0$
$V_{CE0}$	Collector to Emitter Voltage	-20	--	--	V	$I_C = 10\mu A, I_B = 0$
$V_{EBO}$	Emitter-Base Breakdown Voltage	-6.2	--	--	V	$I_E = 10\mu A, I_C = 0^2$
$V_{CC0}$	Collector to Collector Voltage	-80	--	--	V	$I_C = 10\mu A, I_E = 0$
$h_{FE}$	DC Current Gain	50	--	--		$I_C = -1mA, V_{CE} = -5V$
		40	--	--		$I_C = -10mA, V_{CE} = -5V$
		40	--	--		$I_C = -100mA, V_{CE} = -5V$
$V_{CE(SAT)}$	Collector Saturation Voltage	--	--	-1.2	V	$I_C = -100mA, I_B = -10mA$
$I_{EBO}$	Emitter Cutoff Current	--	--	-0.2	nA	$I_E = 0, V_{CB} = -3V$
$I_{CBO}$	Collector Cutoff Current	--	--	-0.2	nA	$I_E = 0, V_{CB} = -20V$
$C_{OBO}$	Output Capacitance	--	--	2	pF	$I_E = 0, V_{CB} = -10V$
$f_T$	Current Gain Bandwidth Product(Current)	--	--	600	MHz	$I_C = -1mA, V_{CE} = -5V$
NF	Narrow Band Noise Figure	--	--	3	dB	$I_C = -100\mu A, V_{CE} = -5V, BW=200Hz, R_G= 10\Omega, f = 1KHz$

Notes:

- Absolute Maximum ratings are limiting values above which serviceability may be impaired
- The reverse base-to-emitter voltage must never exceed 6.2 volts; the reverse base-to-emitter current must never exceed 10µA.



TO-92 (Bottom View)

Available Packages:

LS3550SC in TO-92  
LS3550SC available as bare die

Please contact Micross for full package and die dimensions:

Email: [chipcomponents@micross.com](mailto:chipcomponents@micross.com)  
Web: [www.micross.com/distribution.aspx](http://www.micross.com/distribution.aspx)

