



SamHop Microelectronics Corp.

**STU/D456S**


Ver 1.0

## N-Channel Logic Level Enhancement Mode Field Effect Transistor

PRODUCT SUMMARY		
VDSS	ID	RDS(ON) (mΩ) Max
40V	30A	24 @ VGS=10V
		36 @ VGS=4.5V

### FEATURES

- Super high dense cell design for low RDS(ON).
- Rugged and reliable.
- TO-252 and TO-251 Package.



### ABSOLUTE MAXIMUM RATINGS ( $T_A=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Limit	Units
$V_{DS}$	Drain-Source Voltage	40	V
$V_{GS}$	Gate-Source Voltage	$\pm 20$	V
$I_D$	Drain Current-Continuous <sup>a</sup>	30	A
	$T_C=25^\circ\text{C}$	30	A
	$T_C=70^\circ\text{C}$	24	A
$I_{DM}$	-Pulsed <sup>b</sup>	88	A
$E_{AS}$	Single Pulse Avalanche Energy <sup>d</sup>	30	mJ
$P_D$	Maximum Power Dissipation <sup>a</sup>	42	W
	$T_C=25^\circ\text{C}$	42	W
	$T_C=70^\circ\text{C}$	27	W
$T_J, T_{STG}$	Operating Junction and Storage Temperature Range	-55 to 150	$^\circ\text{C}$

### THERMAL CHARACTERISTICS

$R_{\theta JC}$	Thermal Resistance, Junction-to-Case <sup>a</sup>	3	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient <sup>a</sup>	50	$^\circ\text{C/W}$

Details are subject to change without notice.

Mar,23,2010

# STU/D456S

Ver 1.0

## ELECTRICAL CHARACTERISTICS ( $T_A=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>OFF CHARACTERISTICS</b>						
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V , I <sub>D</sub> =250uA	40			V
I <sub>DS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =32V , V <sub>GS</sub> =0V			1	uA
I <sub>GSS</sub>	Gate-Body Leakage Current	V <sub>GS</sub> = ±20V , V <sub>DS</sub> =0V			±100	nA
<b>ON CHARACTERISTICS</b>						
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250uA	1	1.7	3	V
R <sub>DS(ON)</sub>	Drain-Source On-State Resistance	V <sub>GS</sub> =10V , I <sub>D</sub> =15A		19	24	m ohm
		V <sub>GS</sub> =4.5V , I <sub>D</sub> =12A		27	36	m ohm
g <sub>Fs</sub>	Forward Transconductance	V <sub>DS</sub> =10V , I <sub>D</sub> =15A		34		S
<b>DYNAMIC CHARACTERISTICS <sup>c</sup></b>						
C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> =20V,V <sub>GS</sub> =0V f=1.0MHz		705		pF
C <sub>oss</sub>	Output Capacitance			79		pF
C <sub>rss</sub>	Reverse Transfer Capacitance			61		pF
<b>SWITCHING CHARACTERISTICS <sup>c</sup></b>						
t <sub>D(ON)</sub>	Turn-On Delay Time	V <sub>DD</sub> =20V I <sub>D</sub> =1A V <sub>GS</sub> =10V R <sub>GEN</sub> = 6 ohm		13.3		ns
t <sub>r</sub>	Rise Time			11.5		ns
t <sub>D(OFF)</sub>	Turn-Off Delay Time			18		ns
t <sub>f</sub>	Fall Time			22		ns
Q <sub>g</sub>	Total Gate Charge	V <sub>DS</sub> =20V,I <sub>D</sub> =15A,V <sub>GS</sub> =10V		11.5		nC
		V <sub>DS</sub> =20V,I <sub>D</sub> =15A,V <sub>GS</sub> =4.5V		5.5		nC
Q <sub>gs</sub>	Gate-Source Charge	V <sub>DS</sub> =20V,I <sub>D</sub> =15A, V <sub>GS</sub> =10V		1.5		nC
Q <sub>gd</sub>	Gate-Drain Charge			3.2		nC
<b>DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS</b>						
V <sub>SD</sub>	Diode Forward Voltage <sup>b</sup>	V <sub>GS</sub> =0V,I <sub>S</sub> =1A		0.76	1.3	V
<b>Notes</b>						
a.Surface Mounted on FR4 Board,t ≤ 10sec.						
b.Pulse Test:Pulse Width ≤ 300us, Duty Cycle ≤ 2%.						
c.Guaranteed by design, not subject to production testing.						
d.Starting T <sub>J</sub> =25°C,L=0.5mH,V <sub>DD</sub> = 20V.(See Figure13)						

Mar,23,2010




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature




Figure 5. Gate Threshold Variation with Temperature






Figure 6. Breakdown Voltage Variation with Temperature




V<sub>GS</sub>, Gate-to-Source Voltage(V)

Figure 7. On-Resistance vs. Gate-Source Voltage




V<sub>SD</sub>, Body Diode Forward Voltage(V)

Figure 8. Body Diode Forward Voltage Variation with Source Current



V<sub>DS</sub>, Drain-to-Source Voltage(V)

Figure 9. Capacitance



Q<sub>g</sub>, Total Gate Charge(nC)

Figure 10. Gate Charge




Figure 11. switching characteristics






Figure 12. Maximum Safe Operating Area



Unclamped Inductive Test Circuit

Figure 13a.



Unclamped Inductive Waveforms

Figure 13b.




Figure 14. Normalized Thermal Transient Impedance Curve

# STU/D456S

Ver 1.0


## PACKAGE OUTLINE DIMENSIONS

SYMBOL	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.100	2.500	0.083	0.098
A1	0.350	0.650	0.014	0.026
B	0.400	0.800	0.016	0.031
B1	0.650	1.050	0.026	0.041
B2	0.500	0.900	0.020	0.035
C	0.400	0.600	0.016	0.024
D	5.300	5.700	0.209	0.224
D1	4.900	5.300	0.193	0.209
D2	6.700	7.300	0.264	0.287
D3	7.000	8.000	0.276	0.315
H	13.700	15.300	0.539	0.602
E	6.300	6.700	0.248	0.264
E1	4.600	4.900	0.181	0.193
E2	4.800	5.200	0.189	0.205
L	1.300	1.700	0.051	0.067
L1	1.400	1.800	0.055	0.071
L2	0.500	0.900	0.020	0.035
P	2.300	BSC	0.091	BSC

Mar,23,2010

# STU/D456S

Ver 1.0





Mar,23,2010

# STU/D456S


Ver 1.0

## TO-251 Tube/TO-252 Tape and Reel Data

### TO-251 Tube






### TO-252 Carrier Tape



UNIT:mm

PACKAGE	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
TO-252 (16 mm)	6.96 ±0.1	10.49 ±0.1	2.79 ±0.1	ψ 2	ψ 1.5 + 0.1 - 0	16.0 ±0.3	1.75 ±0.1	7.5 ±0.15	8.0 ±0.1	4.0 ±0.1	2.0 ±0.15	0.3 ±0.05

### TO-252 Reel



UNIT:mm

TAPE SIZE	REEL SIZE	M	N	W	T	H	K	S	G	R	V
16 mm	ψ 330	ψ 330 ± 0.5	ψ 97 ± 1.0	17.0 + 1.5 - 0	2.2	ψ 13.0 + 0.5 - 0.2	10.6	2.0 ± 0.5	---	---	---

Mar,23,2010