


■ Features

- High Luminous LEDs
- 5mm Round Standard Directivity
- Superior Weather-resistance
- UV Resistant Epoxy
- Used 0.8~1.6V DC Drive (Such 1 piece AA or AAA Size Battery)
- Cost Effective (Saves Space and battery Cost)
- Water Clear Type

■ Applications

- Flashlight
- Other Lighting

■ Outline Dimension




■ Absolute Maximum Rating

(Ta=25°C)







Item	Symbol	Value	Unit
DC Forward Voltage	V _F	1.7	V
Oscillator Frequency*	Fled	2.4	Hz
Duty Cycle	Duty	1/12	-
Operating Temperature	Topr	-30 ~ +85	°C
Storage Temperature	Tstg	-30~ +85	°C
Lead Soldering Temperature	Tsol	260°C/5sec	-

■ Directivity



■ Electrical -Optical Characteristics

(Ta=25°C)

Part Number	Color			I _F (mA)		I _v (mcd)*			λD(nm)*			2θ1/2(deg)
				Input	In LED	Min.	Typ.	Max.	Min.	Typ.	Max.	Typ.
				V _F = 1.2V		V _F = 1.2V						
OSW5DR5A31A-W1V	Cool White	W		20±5	7±2	2180	3000	-	X=0.27, Y=0.28			30
OSM5DR5A31A-W1V	Warm White	M		20±5	7±2	1800	2500	-	X=0.45, Y=0.41			
OSB5SR5A31A-W1V	Blue	B		20±5	7±2	1120	1560	-	465	470	475	
OSG5DR5A31A-W1V	Pure Green	G		20±5	7±2	2180	3000	-	520	525	530	
OSY5MR5A31A-W1V	Yellow	Y		20±5	7±2	2180	2800	-	585	590	595	
OSO5MR5A31A-W1V	Orange	O		20±5	7±2	2180	2800	-	600	605	610	
OSR5MR5A31A-W1V	Red	R		20±5	7±2	2180	2800	-	620	625	630	

*1 Tolerance of chromaticity coordinates is ±10%

*2 Tolerance of luminous intensity is ±15%

*3 Tolerance of Frequency is ±20%