Rev	AWO #	Description	Date	Appr
-		RELEASED	1/25/11	

APPROVED: _____

DATE: _____ TITLE: _____







RECOMMENDED PCB LAYOUT

SPECIFICATIONS:
Material:
Insulator: PBT, glass reinforced, rated UL 94V–0
Insulator color: Black
Contacts: Phosphor Bronze
Shield: Copper Alloy, Nickel plated
Contact Plating:
Gold Flash over Nickel underplate on contact area,
Tin over Copper underplate on tails
(See chart for thickness).
Electrical:
Operating voltage: 125 VAC max
Current rating: 1.5 Amps max
Contact Resistance: 30 mohms max. initial
Insulation resistance: 500 Mohms min
Dielectric withstanding voltage: 1000 VAC for 1 minut
Temperature Rating:
Operating temperature: –40°C to +85°C
Environmental:
Lead free, RoHS compliant.
Recommended soldering temp: 235°C for 5 sec.

RoHS COMPLIANT

X	PLATING
0	15 µin Gold
1	30 µin Gold
2	50 µin Gold

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	AY	1/25/11
CHECKED	JL	1/25/11
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE
MODULAR JACK GANGED, 8 PORT, 10P10C

SIZE	PART NO.	REV.
X	MTJG-8-1010TX1-FSG	-

REF: S00167T | SCALE: NTS | SHEET 1 OF 1