

APPLICATION

Home, Small Office, Internet Bar

FEATURES

- Compact size with robust design
- Stylist design with colorful panels for your consideration
- Accepts wide input voltage range (180-264 VAC)
- Provides stable output voltage through boost and buck stabilizer.
- Provides local receptacles for easy of the use
- Provides modem/phone line surge protection

PHASE (ONLY FOR ONLINE UPS)

Phase: 1-phase in / 1-phase out

INPUT

Capacity: 600 VA / 360 W
Voltage: 220 VAC
Voltage Range: 180 - 264 VAC
Frequency Range: 50 Hz

OUTPUT

AC Voltage Regulation (Batt. Mode) : ±8 %
Frequency Range (Batt. Mode): NONE
Waveform (Batt. Mode): Pure Slin Wave

BATTERY

Battery Type: NONE
Battery Number: NONE
Typical Recharge Time: NONE



PROTECTION

Full Protection: Full Protection

PHYSICAL

Output Receptacles: Schuko
Dimension: 166mm(L) x 161mm(W) x 86.7mm(H)
Net Weight (kgs): 1.7

OPERATING ENVIRONMENT

Humidity: 0-90 % RH @ 0- 40°C (non-condensing)
Noise Level: Less than 40dB

This content is subject to change, please refer to specification for more detail.
 FSP reserve the right to change the content without prior notice