


■ Fanless Embedded Controller With Intel® ULV Celeron® 650 MHz, TV-Out, DVI



## Features

- Fanless Design With Intel® ULV Celeron® 650 MHz Processor
- Optional Dual View For Multimedia Application
- MPEG2 Decoding, MPEG4 Playing, TV-out, 6 CH Audio, SPDIF, USB2.0 x 4, Ethernet
- CompactFlash™ Memory And Optional Hard Disk Drive Module
- AT Power Function




## Specifications

System	
Processor	Intel® ULV Celeron® 650 MHz Processor
Memory	DDR SDRAM SODIMM x 1, Max. 512 MB (Optional)
VGA/ Keyboard/Mouse	DB-15 VGA x 1, PS/2 Keyboard & Mouse x 1
Ethernet	10/100Base-TX Ethernet, RJ-45 x 1
SSD	Type II CompactFlash™ x 1
Hard Disk Storage	Optional 2.5" Slim Hard Disk Drive Module
COM	RS-232 x 1, RS-232/422/485 x 1
TV-out	S-video x 1
DVI	DVI-D x 1
Audio	S/PDIF out x1, Mic-in/ Line-in/ Line-out by an External Cable
USB	USB2.0 x 4
System Control	Power on/ off switch x 1, Reset button x 1
LED Indicator	Power LED x 1, Hard Disk Drive active LED x 1
Watchdog Timer	Generates a time-out system reset, setting via software
Power Supply	1. DC Input Internal DC-DC Converter (Standard) Input voltage: 9V DC ~ 30V DC
	2. AC Input External Power Adapter (Optional) Output rating: 36W (+12V@3A) Input voltage: 100V AC ~ 240V AC @ 50 ~ 60Hz
Power Consumption	Intel® Celeron® 650 MHz 1.93A@9V
MTBF (Hours)	60,000
OS Support	Windows® CE .NET 4.2, Windows® XP Embedded, Windows® XP, Windows® 7
Mechanical	
Construction	Rugged Aluminum Alloy chassis
Color	Dark Blue
Mounting	DIN Rail, Wallmount
Dimension	8.4" (W) x 2.5" (H) x 4.2" (D) (212mm x 64mm x 107mm)
Net Weight	4.75 lb (2.16 Kg)
Gross Weight	8.36 lb (3.8 Kg)
Environmental	
Operating Temperature	5°F ~ 131°F (-15°C ~ 55°C) — CompactFlash™ 32°F ~ 122°F (0°C ~ 50°C) — Hard Disk Drive
Storage Temperature	-4°F ~ 158°F (-20°C ~ 70°C) — CompactFlash™ -4°F ~ 140°F (-20°C ~ 60°C) — Hard Disk Drive
Storage Humidity	5~95%@40°C, non-condensing
Vibration	5 g rms/ 5 ~ 500Hz/ random operation (CompactFlash™) 1 g/ 5 ~ 500Hz/ random operation (Hard Disk Drive)
Shock	100g peak acceleration (11 msec. duration) (CompactFlash™) 15g peak acceleration (11 msec. duration) (Hard Disk Drive)
EMC	CE/FCC Class A

# AEC-6830

## Dimension

Unit: mm



## Ordering Information

- **TF-AEC-6830-A1**  
Embedded Controller, Intel® ULV Celeron® 650 MHz CPU, Fanless, DC 9-30V, TV-out, DVI

## Optional Accessories

- **9741681001**  
Hard Disk Drive Kit
- **9741681002**  
AC Input Adapter Kit (36W), Input: AC 90 ~ 264V; Output: DC 12V
- **9741681003**  
DIN Rail Kit
- **9741681004**  
Ultra Cooling Kit
- **9741666643**  
1.8 g rms Vibration Protection Hard Disk Drive Kit for Vehicle
- **9681681000**  
USB to Parallel Port Adapter Kit
- **9789666605**  
USB to 4 COMs Converter
- **9789666606**  
USB to 2 COMs Converter
- **9741681006**  
Easy I/O Display Kit
- **9741681008**  
Slim CD-ROM + 2.5" Hard Disk Drive Kit
- **9783204012**  
Automotive Hard Disk Drive 40G