

## UMK107B7223KAHT



### ■ Features

- Item Summary  
50V, X7R, 0.022  $\mu$ F,  $\pm$ 10%, 0603
- Lifecycle Stage  
Mass Production
- AEC-Q200 qualified
- Standard packaging quantity (minimum)  
Taping paper 4000pcs

### ■ Products characteristics table

CaseSize (EIA/JIS)	0603/1608
Rated Voltage (max)	50V
Capacitance	0.022 $\mu$ F
Capacitance Tolerance	$\pm$ 10%
Resistance	10,000 M $\Omega$ min.
Dielectric Loss Tangent	3.5%MAX
Temperature Characteristics (EIA/JIS)	X7R/-
Temperature Range (EIA/JIS)	-55 to +125 $^{\circ}$ C/-
Capacitance Change (EIA/JIS)	$\pm$ 15/-%
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

### ■ External Dimensions

L	1.6mm $\pm$ 0.10
W	0.8mm $\pm$ 0.10
T	0.8mm $\pm$ 0.10
e	0.35mm $\pm$ 0.25

2015.01.19

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
 Before making final selection, please check product specification.

# Multi Layer Ceramic Capacitor

# TAIYO YUDEN






-Electrical Characteristics Data- 12QA10

RoHS compliance product

## ○UMK107B7223KAHT

50V 1608 X7R 0.022 $\mu$ F +/-10% t=0.9mmMAX

50V 0603 X7R 0.022 $\mu$ F +/-10% t=0.035inchMAX



部品特性は設置環境、測定条件等により変化する場合があります。本データをご使用される際は実際の製品特性に対する参考データとしてご利用ください。また、本データは予告無く追加・削除及び変更を行う場合があります。ご注文の際は、納入仕様書のご確認をお願いします。

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.

TAIYO YUDEN reserves the right to make change to the Date at any time without notice.

Before making final selection, please check product specification