



"CARRIER CLASS" POWER OVER ETHERNET SYSTEM

The POE-55iG-AFI is an advanced 802.3af compliant, non-proprietary power supply/injector. The power supply is autoranging on the input and has a regulated voltage output with overload and short-circuit protection. It functions with any equipment compliant with the IEEE 802.3af POE standards. The POE-55iG-AFI does not include the intelligent detection algorithms detailed in the 802.3af spec, meaning it will power up any device connected to it. The power is supplied on Ethernet pins 4/5 (V+) and 7/8 (V-) and comes complete with a standard North American 115 VAC power cord. International cords are available upon request.

Using power over Ethernet to power remote devices has several advantages including:

- The power supply can be centrally located where it can be attached to an uninterruptible power supply.
- The user has the ability to easily power on and reset the attached equipment from a remote location.
- There is no need to run additional power cabling to the device as power can be supplied over the CAT5 Ethernet cable.
- The power supply can power a remote device up to 300 feet away, limited only by the Ethernet standard.

FEATURES

- "Carrier class" power over Ethernet system
- Autoranging power supply/ injector
- Built-in Ethernet surge protection to prevent equipment damage
- Overload and short-circuit protection
- Minimum cross-talk and insertion loss
- Advanced switching technology – runs cool
- Powers clients that accept power on unused Ethernet pins 4, 5, 7, 8
- FCC and CE approved
- Current indicator (CI) option available

MARKETS

- Remote routers, access points, and bridges
- Remote networking equipment
- Remote camera systems
- 400 MHz to 10 GHz systems
- SOHO equipment
- IP phone systems
- WiMAX

global solutions: local support.™

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

SPECIFICATIONS

Input Voltage:	90 – 264 VAC @ 47 – 63 Hz
Input Current:	0.85 A @ 120 VAC 0.93 A @ 230 VAC
Efficiency:	78% min at Full Load, 120 Vac and 230 Vac Input Voltage
Output Voltage:	+55 V
Maximum Load:	0.55 A Min
Power	30 W
Minimum Load:	0.01 A Min
Output Noise:	1%
Output Ripple:	1%
Line Regulation:	1%
Load Regulation:	5%
Short Circuit Protection:	Output short GND terminal will not damage the power supply and will auto-reset. Input has fuse protection.
Safety Standards:	Meets UL1950, CSA 22.2 and TUV EN60950
EMC:	Meets FCC Class B , NE55022 Class B
Over Current:	120% ~ 160% @120 Vac Input F.L
Operating Temperature:	-25 to +65°C
Storage Temperature:	-40 to +80°C
Operating Humidity:	5% to 90%
Cooling:	Free air cooling
Size (L x W x H):	125 x 75 x 38 mm
LED (Green):	Include PWR-OK

Note 1: Noise bandwidth is from DC to 20 Mhz. Ripple & Noise is measured by Paralleling a 0.1 uF metalize capacitor on the test point.

RJ-45 INPUT (DATA ONLY)			RJ-45 OUTPUT (DATA & POWER)	
Pin	Symbol	Description	Symbol	Description
1	RX+	Data Receive	RX+	Data Receive
2	RX-	Data Receive	RX-	Data Receive
3	TX+	Data Transmit	TX+	Data Transmit
4	Data	Data	+Vdc	power(+)+Data
5	Data	Data	+Vdc	power(+)+Data
6	TX-	Data Transmit	TX-	Data Transmit
7	Data	Data	-Vdc	power(-)+Data
8	Data	Data	-Vdc	power(-)+Data

Note : 1. DC output gnd and Vin+/- should not be shorted to ground(FG).

ANT-DS-POE-Gigabit-AF 0611

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2011 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.



Power Supply Inserter AC Power IN (90-264VAC)@120V/230



Power Supply Inserter Data IN Power Supply Inserter Data/POE OUT