

# MDP13N50B / MDF13N50B

## N-Channel MOSFET 500V, 13.0 A, 0.5Ω

### General Description

The MDP/F13N50B uses advanced Magnachip's MOSFET Technology, which provides low on-state resistance, high switching performance and excellent quality.


MDP/F13N50B is suitable device for SMPS, HID and general purpose applications.

### Features

- $V_{DS} = 500V$
- $I_D = 13.0A$  @  $V_{GS} = 10V$
- $R_{DS(ON)} \leq 0.5\Omega$  @  $V_{GS} = 10V$

### Applications


- Power Supply
- PFC
- Ballast



TO-220<sub>4</sub>  
MDP Series<sub>4</sub>



TO-220F<sub>4</sub>  
MDF Series<sub>4</sub>



### Absolute Maximum Ratings (Ta = 25°C)

Characteristics		Symbol	MDP13N50B	MDF13N50B	Unit
Drain-Source Voltage		$V_{DSS}$	500		V
Gate-Source Voltage		$V_{GSS}$	±30		V
Continuous Drain Current	$T_C=25^\circ C$	$I_D$	13	13*	A
	$T_C=100^\circ C$		8.2	8.2*	A
Pulsed Drain Current <sup>(1)</sup>		$I_{DM}$	52	52*	A
Power Dissipation	$T_C=25^\circ C$	$P_D$	187	41	W
	Derate above 25 °C		1.49	0.33	W/°C
Repetitive Avalanche Energy <sup>(1)</sup>		$E_{AR}$	18.7		mJ
Peak Diode Recovery $dv/dt$ <sup>(3)</sup>		$dv/dt$	4.5		V/ns
Single Pulse Avalanche Energy <sup>(4)</sup>		$E_{AS}$	580		mJ
Junction and Storage Temperature Range		$T_J, T_{stg}$	-55~150		°C

\* Id limited by maximum junction temperature

### Thermal Characteristics

Characteristics	Symbol	MDP13N50B	MDF13N50B	Unit
Thermal Resistance, Junction-to-Ambient <sup>(1)</sup>	$R_{\theta JA}$	62.5	62.5	°C/W
Thermal Resistance, Junction-to-Case <sup>(1)</sup>	$R_{\theta JC}$	0.67	3.05	

## Ordering Information

Part Number	Temp. Range	Package	Packing	RoHS Status
MDP13N50BTH	-55~150°C	TO-220	Tube	Halogen Free
MDF13N50BTH	-55~150°C	TO-220F	Tube	Halogen Free

## Electrical Characteristics (Ta = 25°C)

Characteristics	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Static Characteristics</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$I_D = 250\mu A, V_{GS} = 0V$	500	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	2.0	-	4.0	
Drain Cut-Off Current	$I_{DSS}$	$V_{DS} = 500V, V_{GS} = 0V$	-	-	1	$\mu A$
Gate Leakage Current	$I_{GSS}$	$V_{GS} = \pm 30V, V_{DS} = 0V$	-	-	100	nA
Drain-Source ON Resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 6.5A$	-	0.39	0.5	$\Omega$
Forward Transconductance	$g_{fs}$	$V_{DS} = 40V, I_D = 6.5A$	-	13	-	S
<b>Dynamic Characteristics</b>						
Total Gate Charge	$Q_g$	$V_{DS} = 400V, I_D = 13.0A, V_{GS} = 10V^{(3)}$	-	27	-	nC
Gate-Source Charge	$Q_{gs}$		-	6.3	-	
Gate-Drain Charge	$Q_{gd}$		-	8.6	-	
Input Capacitance	$C_{iss}$	$V_{DS} = 25V, V_{GS} = 0V, f = 1.0MHz$	-	1459	-	pF
Reverse Transfer Capacitance	$C_{rss}$		-	7.4	-	
Output Capacitance	$C_{oss}$		-	174	-	
Turn-On Delay Time	$t_{d(on)}$	$V_{GS} = 10V, V_{DS} = 250V, I_D = 13.0A, R_G = 25\Omega^{(3)}$	-	21	-	ns
Rise Time	$t_r$		-	47	-	
Turn-Off Delay Time	$t_{d(off)}$		-	131	-	
Fall Time	$t_f$		-	54	-	
<b>Drain-Source Body Diode Characteristics</b>						
Maximum Continuous Drain to Source Diode Forward Current	$I_S$		-	13	-	A
Source-Drain Diode Forward Voltage	$V_{SD}$	$I_S = 13.0A, V_{GS} = 0V$	-	-	1.4	V
Body Diode Reverse Recovery Time	$t_{rr}$	$I_F = 13.0A, di/dt = 100A/\mu s^{(3)}$	-	325	-	ns
Body Diode Reverse Recovery Charge	$Q_{rr}$		-	2.9	-	$\mu C$

Note :

- Pulse width is based on  $R_{\theta JC}$  &  $R_{\theta JA}$  and the maximum allowed junction temperature of 150°C.
- Pulse test: pulse width  $\leq 300\mu s$ , duty cycle  $\leq 2\%$ , pulse width limited by junction temperature  $T_{J(MAX)} = 150^\circ C$ .
- $I_{SD} \leq 13.0A$ ,  $di/dt \leq 200A/\mu s$ ,  $V_{DD} \leq BV_{DSS}$ ,  $R_G = 25\Omega$ , Starting  $T_J = 25^\circ C$
- $L = 6.2mH$ ,  $I_{AS} = 13.0A$ ,  $V_{DD} = 50V$ ,  $R_G = 25\Omega$ , Starting  $T_J = 25^\circ C$




Fig.1 On-Region Characteristics




Fig.2 On-Resistance Variation with Drain Current and Gate Voltage




Fig.3 On-Resistance Variation with Temperature




Fig.4 Breakdown Voltage Variation vs. Temperature




Fig.5 Transfer Characteristics







Fig.6 Body Diode Forward Voltage Variation with Source Current and Temperature




**Fig.7 Gate Charge Characteristics**




**Fig.8 Capacitance Characteristics**




**Fig.9 Maximum Safe Operating Area MDP13N50B (TO-220)**




**Fig.10 Maximum Drain Current vs. Case Temperature**




**Fig.11 Transient Thermal Response Curve MDP13N50B (TO-220)**




**Fig.12 Single Pulse Maximum Power Dissipation – MDP13N50B (TO-220)**



**Fig.13 Maximum Safe Operating Area  
MDF13N50B (TO-220F)**



**Fig.14 Single Pulse Maximum Power  
Dissipation – MDF13N50B (TO-220F)**




**Fig.15 Transient Thermal Response Curve  
MDF13N50B (TO-220F)**

## Physical Dimensions

### 3 Leads, TO-220

Dimensions are in millimeters unless otherwise specified




Symbol	Min	Nom	Max
A	3.56		4.83
A1	0.50		1.40
A2	2.03		2.92
b	0.38	0.69	1.02
b2	1.14	1.45	1.78
c	0.36		0.61
D	14.22		16.51
e	2.54 TYP		
E	9.65		10.67
H1	5.84		6.86
L	12.70		14.73
L1			6.35
$\phi P$	3.53		4.09
Q	2.54		3.43

**Physical Dimension**

**3 Leads, TO-220F**

Dimensions are in millimeters unless otherwise specified



Symbol	Min	Nom	Max
A	4.50		4.93
b	0.63		0.91
b1	1.15		1.47
C	0.33		0.63
D	15.47		16.13
E	9.60		10.71
e		2.54	
F	2.34		2.84
G	6.48		6.90
L	12.24		13.72
L1	2.79		3.67
Q	2.52		2.96
Q1	3.10		3.50
$\phi R$	3.00		3.55

**Worldwide Sales Support Locations****U.S.A****Sunnyvale Office**

787 N. Mary Ave. Sunnyvale  
 CA 94085 U.S.A  
 Tel : 1-408-636-5200  
 Fax : 1-408-213-2450  
 E-Mail : usasales@magnachip.com

**U.K**

Knyvett House The Causeway,  
 Staines Middx, TW18 3BA,U.K.  
 Tel : +44 (0) 1784-895-000  
 Fax : +44 (0) 1784-895-115  
 E-Mail : uksales@magnachip.com

**Japan****Osaka Office**

3F, Shin-Osaka MT-2 Bldg 3-5-36  
 Miyahara Yodogawa-Ku  
 Osaka, 532-0003 Japan  
 Tel : 81-6-6394-9160  
 Fax : 81-6-6394-9150  
 E-Mail : osakasales@magnachip.com

**Taiwan R.O.C**

2F, No.61, Chowize Street, Nei Hu  
 Taipei, 114 Taiwan R.O.C  
 Tel : 886-2-2657-7898  
 Fax : 886-2-2657-8751  
 E-Mail : taiwansales@magnachip.com

**China****Hong Kong Office**

Suite 1024, Ocean Centre 5 Canton Road,  
 Tsim Sha Tsui Kowloon, Hong Kong  
 Tel : 852-2828-9700  
 Fax : 852-2802-8183  
 E-Mail : chinasales@magnachip.com

**Shenzhen Office**

Room 2003B, 20/F  
 International Chamber of Commerce Tower  
 Fuhua Road3 CBD, Futian District, China  
 Tel : 86-755-8831-5561  
 Fax : 86-755-8831-5565  
 E-Mail : chinasales@magnachip.com

**Shanghai Office**

Room E, 8/F, Liaoshen International Building 1068  
 Wuzhong Road, (C) 201103  
 Shanghai, China  
 Tel : 86-21-6405-1521  
 Fax : 86-21-6505-1523  
 E-Mail : chinasales@magnachip.com

**Korea**

891, Daechi-Dong, Kangnam-Gu  
 Seoul, 135-738 Korea  
 Tel : 82-2-6903-3451  
 Fax : 82-2-6903-3668 ~9  
 Email : koreasales@magnachip.com

**DISCLAIMER:**

The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.

MagnaChip reserves the right to change the specifications and circuitry without notice at any time. MagnaChip does not consider responsibility for use of any circuitry other than circuitry entirely included in a MagnaChip product. **MagnaChip** is a registered trademark of MagnaChip Semiconductor Ltd.