


NEW PRODUCT

Features

- Low On-Resistance
- Low Gate Threshold Voltage
- Low Input Capacitance
- Fast Switching Speed
- **Lead Free By Design/RoHS Compliant (Note 2)**
- **ESD Protected Gate**
- **"Green" Device (Note 4)**
- **Qualified to AEC-Q101 standards for High Reliability**

Mechanical Data

- Case: SC-59
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture sensitivity: Level 1 per J-STD-020C
- Terminals: Finish — Matte Tin annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Terminal Connections: See Diagram
- Marking Information: See Page 4
- Ordering & Date Code Information: See Page 4
- Weight: 0.008 grams (approximate)



SC-59		
Dim	Min	Max
A	0.30	0.50
B	1.40	1.80
C	2.50	3.00
D	0.85	1.05
E	0.30	0.70
G	1.70	2.10
H	2.70	3.10
J	—	0.10
K	1.00	1.40
L	0.55	0.70
M	0.10	0.35
α	0°	8°
All Dimensions in mm		

Maximum Ratings @T_A = 25°C unless otherwise specified



Characteristic	Symbol	Value	Unit
Drain-Source Voltage	V _{DSS}	-30	V
Gate-Source Voltage	V _{GSS}	±20	V
Drain Current (Note 1) Steady State	I _D	-0.7	A
Pulsed Drain Current (Note 3)	I _{DM}	-2.8	A
Total Power Dissipation (Note 1)	P _d	500	mW
Thermal Resistance, Junction to Ambient	R _{θJA}	250	°C/W
Operating and Storage Temperature Range	T _i , T _{STG}	-65 to +150	°C

- Notes:
1. Device mounted on FR-4 PCB.
 2. No purposefully added lead.
 3. Pulse width ≤10μS, Duty Cycle ≤1%.
 4. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.

Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 5)						
Drain-Source Breakdown Voltage	BV_{DSS}	-30	—	—	V	$V_{GS} = 0V, I_D = -250mA$
Zero Gate Voltage Drain Current	I_{DSS}	—	—	-10	μA	$V_{DS} = -30V, V_{GS} = 0V$
Gate-Body Leakage	I_{GSS}	—	—	± 10	μA	$V_{GS} = \pm 20V, V_{DS} = 0V$
ON CHARACTERISTICS (Note 5)						
Gate Threshold Voltage	$V_{GS(th)}$	-1.0	—	-3.0	V	$V_{DS} = -10V, I_D = -1.0mA$
Static Drain-Source On-Resistance	$R_{DS(ON)}$	—	0.20 0.35	0.25 0.45	Ω	$V_{GS} = -10V, I_D = -0.4A$ $V_{GS} = -4.5V, I_D = -0.4A$
Forward Transfer Admittance	$ Y_{fs} $	—	1	—	S	$V_{DS} = -10V, I_D = 0.4A$
Diode Forward Voltage (Note 5)	V_{SD}	—	-0.8	-1.1	V	$V_{GS} = 0V, I_S = -0.7A$
DYNAMIC CHARACTERISTICS						
Input Capacitance	C_{iss}	—	160	—	pF	$V_{DS} = -10V, V_{GS} = 0V$ $f = 1.0MHz$
Output Capacitance	C_{oss}	—	120	—	pF	
Reverse Transfer Capacitance	C_{rss}	—	50	—	pF	
SWITCHING CHARACTERISTICS						
Turn-On Delay Time	$t_{D(ON)}$	—	10	—	ns	$V_{DD} = -10V, I_D = -0.4A,$ $V_{GS} = -5.0V, R_{GEN} = 50\Omega$
Turn-Off Delay Time	$t_{D(OFF)}$	—	25	—	ns	
Turn-On Rise Time	t_r	—	25	—	ns	
Turn-Off Fall Time	t_f	—	40	—	ns	

Notes: 5. Short duration test pulse used to minimize self-heating effect.






Fig. 3 On-Resistance vs. Gate Voltage




Fig. 4 On-Resistance vs. Drain Current




Fig. 5 On-Resistance Variation with Temperature




Fig. 6 Gate-Source Threshold Voltage with Temperature




Fig. 7 Reverse Drain Current vs. Source-Drain Voltage





Fig. 8: Typical Junction Capacitance

Ordering Information (Note 6)

Device	Packaging	Shipping
DMP3030SN-7	SC-59	3000/Tape & Reel

Notes: 6. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information



PS2 = Product Type Marking Code
 YM = Date Code Marking
 Y = Year ex: T = 2006
 M = Month ex: 9 = September

Date Code Key

Year	2006	2007	2008	2009	2010	2011	2012
Code	T	U	V	W	X	Y	Z

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.