

Part Number: C3129

Revision Level: 0

Date: 7/7/2007

**2C 12 19/0.0185 BC FLEX FLEX**

**TYPE CL3P**

**A. CONSTRUCTION**

**DIAMETERS**

Conductor:	#12 AWG 19/0.0185 Bare Copper	0.092" nom.
Insulation:	0.010" Wall FLEXGUARD*	0.112" nom.
Cable:	2 Conductors @ 4.00" LHL.	0.184" nom.
Jacket:	0.015" Wall FLEXGUARD* - Natural -Plenum ripcord under jacket.	0.214" +/- 0.011"
Print Legend:	<b>CAROL (R) 12 AWG -- C3129 -- 75C E60233-8 (UL) CL3P -- MADE IN USA</b> <b>DATE CODE (PRINT EVERY 2 FT)</b>	

**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 13	Type CL3P

**C. ELECTRICAL PROPERTIES**

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (Vrms):	150 Vrms (CL3P)
CONDUCTOR D.C. RESISTANCE:	1.6 Ohms/1000 ft. nom. @ 20C

**D. COLOR CODE** (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

\*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.