


EFRP-S2207HPM

1U 200W Redundant Network Power

Features:

- 1U Slim (ERP1U) Form Factor
- 200W with ATX Outputs
- Max. 85% Power Efficiency
- PMBus Support
- 1+1 Redundancy / Load Sharing



General Specification

- Input Range: 100 to 240 VAC, +/-10%
- Power Factor: ≥0.95 minimum
- Efficiency: ≥80% @ 115VAC
- Hold Up Time: 16ms @ 80% Load
- Short Circuit Protection
- Over Current Protection
- Over Voltage Protection
- No load Operation
- Over Temperature Protection
- MTBF >100,000 Hours@25°C
- Operating Temperature: 0 to 50 °C
- Operating Humidity: 20 to 90 %
- EMI/RFI: CE, FCC class B
- Safety: UL, CB, TUV, CCC, BSMI

Input and Output Characteristics

Input			Output						
Voltage	Frequency	Current	Load	+3.3V	+5V	+12V	-12V	-5V	+5VSB
100~240 VAC	47~63Hz	3~1.5A	Max.Load	20A	20A	16A	0.5A		2A
			Min.Load	0.5A	0.5A	0.8A	0A		0A

Note:1: The +3.3 & +5 Volt total outputs shall not exceed 120W.

2: Noise bandwidth is from DC to 20 MHz


Ripple and Noise

Output	+3.3V	+5V	+12V	-12V	5Vsb
Load Regulation	±5%	± 5%	± 5%	± 5%	± 5%
Line Regulation	± 1%	± 1%	± 1%	± 1%	± 1%
Ripple & Noise	60mV	60mV	120mV	120mV	60mV

Mechanical

Outline Dimension: 106x41.5x260(mm)

Outline Drawing



©ETASIS Electronic Corporation. All rights reserved. ETASIS Electronics Corporation reserves the right to make changes to their products, specification, or to discontinue any product and its service at anytime without notice. The information and specification from ETASIS is believed to be accurate and reliable. However, ETASIS assumes no responsibility for any business loss due to specification changes. ETASIS products are not designed to be used in system deemed to be critical, or in any system wherein failure or malfunction could result in injury or death.