


Ceramic, AxiMax, 1000 pF, 5%, 100 V, COG, AxiMax, Commercial Standard



#### Dimensions

<b>D</b>	2.31mm MAX
<b>L</b>	4.32mm MAX
<b>LL</b>	25.4mm +0.025/-0.076mm
<b>F</b>	0.51mm +0.025/-0.076mm

#### Packaging Specifications

<b>Packaging:</b>	T&R, 305mm
<b>Packaging Quantity:</b>	5000

#### General Information

<b>Series:</b>	AxiMax
<b>Description:</b>	AxiMax, Commercial Standard
<b>RoHS:</b>	Yes
<b>Termination:</b>	Tin
<b>Failure Rate:</b>	N/A
<b>Halogen Free:</b>	Yes

#### Specifications

<b>Capacitance:</b>	1000 pF
<b>Capacitance Tolerance:</b>	5%
<b>Voltage DC:</b>	100 VDC
<b>Dielectric Withstanding Voltage:</b>	250 V
<b>Temperature Range:</b>	-55/+125C
<b>Temperature Coefficient:</b>	COG
<b>Dissipation Factor:</b>	0.1% 25C
<b>Aging Rate:</b>	0% Loss/Decade Hour
<b>Insulation Resistance:</b>	100 GOhms