

03

SV ...-8


Circular connectors with threaded joint M16 acc. to IEC 61076-2-106, IP40/IP67/IP68



Plug acc. to IEC 61076-2-106, IP 40, straight version, with threaded joint, solder terminals and short bend protection

03

SV ...-8



Environmental conditions

Temperature range -40 °C/+85 °C

Materials

Insulating body	PA GF, V-0 according to UL94
Contact pin	CuZn, silver-plated and flash gold-plated (3-8 poles) CuZn, pre-nickel and gold-plated (12 poles)
Ground contact spring	CuZn, pre-nickel and tin-plated
Sleeve	PC, HB according to UL94
Strain relief	steel, nickel-plated
Housing	CuZn, nickel-plated
Knurled screw	CuZn, nickel-plated
Bend protection sleeve	TPE
Screw	steel, nickel-plated

Mechanical data

Protection class IP40¹

¹ according to IEC DIN EN 60529, only in locked condition with an appropriate counterpart

Connectable conductors for solder area


Section	≤ 0.75 mm ² (AWG 20) (3-8 poles) ≤ 0.25 mm ² (AWG 24) (12 poles)
Cable diameter	6-8 mm

Electrical data (at T_{amb} 20 °C)


Rated current	5 A (T _{amb} 40 °C, 3-8 poles) 3 A (T _{amb} 40 °C, 12 poles)
Rated voltage	with pollution degree 1: 300 V (versions 30, 40, 50/6, 60, 70) 100 V (versions 50, 71, 80, 81) 160 V (Polbild 120) with pollution degree 2: 250 V (versions 30, 40) 32 V (versions 50, 71, 80, 81) 160 V (versions 50/6, 60, 70, 120)
Rated impulse voltage	1500 V (versions 30, 40, 50/6, 60, 70, 120) 500 V (versions 50, 71, 80, 81)
Material group	II (IEC)/0 (UL) (CTI ≥ 550)
Overvoltage category	I
Insulation resistance	> 100 MΩ

03


SV ...-8




03-a
SV 30-8




04-a
SV 40-8




05-b
SV 50-8




05-a
SV 50/6-8




06-a
SV 60-8




07-a
SV 70-8




07-b
SV 71-8



SV 80-8



08-a
SV 81-8



12-a
SV 120-8

Associated products

Counterparts

☞ 030398

☞ KGR

☞ KV ...-8

☞ KFR

☞ KGV

☞ WKV

☞ KfV

☞ KV

Accessories

☞ 0383

☞ 038399

☞ 038899

*a 12 pole version Ø 1.0 mm

*b cup-shaped solder terminal

03

SV ...-8

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
SV 30-8	3	50	500
SV 40-8	4	50	500
SV 50-8	5	50	500
SV 50/6-8	5	50	500
SV 60-8	6	50	500
SV 70-8	7	50	500
SV 71-8	7	50	500
SV 80-8	8	50	500
SV 81-8	8	50	500
SV 120-8	12	50	500

Packaging:

pre-assembled, in a cardboard box