


CC45SL3AD560JYNNA



<b>Applications</b>	Commercial Grade
<b>Feature</b>	<div style="display: flex; flex-direction: column; gap: 5px;"> <div><span style="background-color: #f08080; padding: 2px;">High</span> High Voltage (1000V and over)</div> <div><span style="background-color: #9370db; padding: 2px;">Low D</span> Low Dissipation</div> <div><span style="background-color: #9acd32; padding: 2px;">Halogen-free</span> Halogen-free</div> </div>
<b>Series</b>	CC45
<b>Status</b>	Production



Size	
Diameter(D)	5.50mm Max.
Thickness(T)	5.00mm Max.
Lead Gap(F)	5.00mm ±1.50mm
Lead Diameter(d)	0.60mm ±0.05mm

Electrical Characteristics	
Capacitance	56pF ±5%
Rated Voltage	1kVDC
Withstanding Voltage	2kVDC
Temperature Characteristic	SL(0+350,-1000ppm/°C)
Q (Min.)	1000
Insulation Resistance (Min.)	10000MΩ



Other	
Soldering Method	Wave (Flow) Iron Soldering
Lead Length / Package Type	5mm for Bulk
AEC-Q200	No
Package Quantity	1000pcs

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.

CC45SL3AD560JYNNA



Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)



! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.