



SC3524, SC3528, SC3540

35A, 20-24V, 24-32V, 38-42V

AVALANCHE SOZA CELL

SC

FEATURES


- .High current capability
- .Low forward voltage drop
- Low leakage current
- High surge current capability

MECHANICAL DATA

Small copper: $\varphi 0.258(6.55) \times 0.0394(1.0)$ Thick

Large copper: $\varphi 0.284(7.22) \times 0.0295(0.75)$ Thick

Outline information: $\varphi 0.284(7.22) \times 0.0866(2.2)$ Thick



Dimension in inches(millimeters)

Rating at 25°C Ambient temp. Unless otherwise specified. Single phase, half sine wave, 60HZ, resistive or inductive load.

For capacitive load, derate current by 20%

	SYMBOL	SC3524	SC3528	SC3540	UNITS
Maximum Current Peak Reverse Voltage	VRRM	16	20	34	Volts
Working Peak Reverse Voltage	VRWM	16	20	34	Volts
Maximum DC Blocking Voltage	VDC	16	20	34	Volts
Breakdown voltage Min@ IBR=100mA/TA=25°C	VBRL	20	24	38	Volts
Breakdown voltage Max@ IBR=100mA/TA=25°C	VBRH	24	32	42	Volts
TL=125°C Maximum Average Forward Rectified Current	I(AV)	35			Amps
Peak Forward Surge Current 8.3ms Single Sine-wave on Rated Load (JEDEC Method)	IFSM	400			Amps
Maximum Instantaneous Forward Voltage Drop at 35A DC	VF	1.0			Volts
TA=25°C Maximum DC Reverse Current at Rated DC Blocking Voltage	IR	0.2			uA
IF=10mA Forward Voltage Temperature Coefficient	VFTS	2			mV/°C
Operating AND Storage Temperature Range	TSTG/ TJ	-55 to +150			°C

NOTE: 1. Measured at 1 MHz and Applied Reverse Voltage of 4.0 Volts D.C.

RATING AND CHARACTERISTIC CURVES SC3524 THRU SC3540

FIG. 1 – MAXIMUM AVERAGE FORWARD CURRENT DERATING




FIG. 2 – MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 – PULSE WAVEFORM




FIG. 4 – TYPICAL FORWARD CHARACTERISTICS




FIG. 5 – PULSE RATING CURVE

