



Material:

- 1.Cable: #28,UL2919, 3COAX+4C+1+AL/MY+B,O.D:8.1
- 2.Connector: HD15M, 9th Empty, Black
- 3.Thumbscrew:#4-40UNC, E32
- 4.Black Heat Shrink:∅1.5x15:6PCS ∅3x8:6PCS
- 5.Copper Size:30X50

Note:

- 1.Total Length: SEE "ITEM NO."
- 2.Color: Beige
- 3.Molded Type
- 4.360° Solder

Configuration:

| HD15M | | HD15M |
|--------|---------------|--------|
| 1 | Red(Coax) | 1 |
| 6 | Red(Ground) | 6 |
| 2 | Green(Coax) | 2 |
| 7 | Green(Ground) | 7 |
| 3 | Blue(Coax) | 3 |
| 8 | Blue(Ground) | 8 |
| 4 | Brown | 4 |
| 5 | Black | 5 |
| 13 | Orange | 13 |
| 14 | White | 14 |
| Shield | (Braid) | Shield |



| | |
|---------|---|
| ITEM NO | AK3760-R (3 Meters) |
| | AK3770-R (5 Meters) |
| | AK3780-R (10 Meters) |
| TITLE | PREMIUM VGA Monitor Connection Cable, HD DSUB 15-Pin Male to HD DSUB 15-Pin Male |

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
© Copyright 2008 by Assmann Electronic Components
All International Rights Reserved