

isc Silicon PNP Power Transistor

2SB719

DESCRIPTION



- High Collector-Emitter Breakdown Voltage-
: $V_{(BR)CEO} = -160V(\text{Min})$
- Wide Area of Safe Operation
- Complement to Type 2SD759

APPLICATIONS

- Designed for power amplifier and TV vertical deflection output applications.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

| SYMBOL | PARAMETER | VALUE | UNIT |
|-----------|---|---------|------------------|
| V_{CBO} | Collector-Base Voltage | -160 | V |
| V_{CEO} | Collector-Emitter Voltage | -160 | V |
| V_{EBO} | Emitter-Base Voltage | -5.0 | V |
| I_C | Collector Current-Continuous | -2 | A |
| I_{CM} | Collector Current-Peak | -3 | A |
| P_C | Total Power Dissipation@ $T_C=25^\circ\text{C}$ | 25 | W |
| T_J | Junction Temperature | 150 | $^\circ\text{C}$ |
| T_{stg} | Storage Temperature Range | -55~150 | $^\circ\text{C}$ |



isc Silicon PNP Power Transistor**2SB719****ELECTRICAL CHARACTERISTICS****T_C=25°C unless otherwise specified**

| SYMBOL | PARAMETER | CONDITIONS | MIN | TYP. | MAX | UNIT |
|----------------------|--------------------------------------|---|------|------|------|------|
| V _{(BR)CEO} | Collector-Emitter Breakdown Voltage | I _C = -5mA; I _B = 0 | -160 | | | V |
| V _{(BR)CBO} | Collector-Base Breakdown Voltage | I _C = -0.1mA; I _E = 0 | -160 | | | V |
| V _{(BR)EBO} | Emitter-Base Breakdown Voltage | I _E = -0.1mA; I _C = 0 | -5 | | | V |
| V _{CE(sat)} | Collector-Emitter Saturation Voltage | I _C = -500mA; I _B = -50mA | | | -1.0 | V |
| V _{BE(sat)} | Base-Emitter Saturation Voltage | I _C = -500mA; I _B = -50mA | | | -1.5 | V |
| I _{CBO} | Collector Cutoff Current | V _{CB} = -150V; I _E = 0 | | | -10 | μ A |
| I _{EBO} | Emitter Cutoff Current | V _{EB} = -3.0V; I _C =0 | | | -10 | μ A |
| h _{FE} | DC Current Gain | I _C = -150mA; V _{CE} = -5V | 35 | | 200 | |
| f _T | Current-Gain—Bandwidth Product | I _C = -100mA; V _{CE} = -10V | | 100 | | MHz |

◆ **h_{FE} Classifications**

| A | B | C |
|-------|--------|---------|
| 35-70 | 60-120 | 100-200 |