

83265 Coax - 50 Ohm Coax

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
--	--

Description:

30 AWG stranded (7x38) .012" silver-plated copper-covered steel conductor, TFE PTFE insulation, silver-plated copper braid shield (96% coverage), FEP jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	178B/U
AWG	30
Stranding	7x38
Conductor Diameter	.012 in.
Conductor Material	SPCCS - Silver Plated Copper Covered Steel

INSULATION:

Insulation Material Trade Name	PTFE
Insulation Material	TFE - Tetrafluoroethylene
Insulation Diameter	.033 in.

OUTER SHIELD:

Outer Shield Type	Braid
Outer Shield Material	SPC - Silver Plated Copper
Outer Shield % Coverage	96 %

OUTER JACKET:

Outer Jacket Material	FEP - Fluorinated Ethylene Propylene
-----------------------	--------------------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.071 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-70°C To +200°C
Non-UL Temperature Rating	200°C
Bulk Cable Weight	6 lbs/1000 ft.
Max. Recommended Pulling Tension	12 lbs.
Min. Bend Radius (Install)	1 in.

83265 Coax - 50 Ohm Coax

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

EU CE Mark (Y/N)	No
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
Military Specification	M17/169-00001

FLAME TEST:

UL Flame Test	UL1685 UL Loading, VW-1
---------------	-------------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	50 Ohms
Nom. Inductance	0.072 μ H/ft
Nom. Capacitance Conductor to Shield	29.0 pF/ft
Nominal Velocity of Propagation	69.5 %
Nominal Delay	1.46 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	244.0 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg.C	14.6 Ohms/1000 ft

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			2.6
	10			5.6
	50			10.5
	100			14.0
	200			19.0
	400			28.0
	700			37.0
	900			42.5
	1000			46.0

Nom. Power Rating :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Power Rating (W)
	50			380
	100			253
	200			170
	400			113
	700			81
	900			70
	1000			66

Max. Operating Voltage - Other :

83265 Coax - 50 Ohm Coax

Other Voltage	Description
Military Specification	750 V RMS

NOTES:

Notes	PTFE is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.
-------	--

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
83265 009100	#30 COAX RG-178B/U	100	0.8	WHITE	E
83265 0091000	#30 COAX RG-178B/U	1000	6	WHITE	E
83265 009500	#30 COAX RG-178B/U	500	3.5	WHITE	E

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'

Revision Number: 2 Revision Date: 07-12-2005

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.