



CHENMKO ENTERPRISE CO.,LTD

SURFACE MOUNT

SCHOTTKY BARRIER RECTIFIER

VOLTAGE RANGE 20 - 60 Volts CURRENT 3.0 Amperes

Lead free devices

SCM32PT

THRU

SCM36PT

FEATURES

- * Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- * For surface mounted applications
- * Low profile package
- * Built-in strain relief
- * Metal silicon junction, majority carrier conduction
- * Low power loss, high efficiency
- * High current capability, low forward voltage drop
- * High surge capability
- * For use in low voltage high frequency inverters, free wheeling, and polarity protection applications
- * High temperature soldering guaranteed : 260°C/10 seconds at terminals

MECHANICAL DATA

Case: JEDEC SMC molded plastic

Terminals: Solder plated, solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Weight: 0.007 ounce 0.25 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS


Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%.



SMC



Dimensions in inches and (millimeters)

SMC

MAXIMUM RATINGS (At TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	SCM32PT	SCM33PT	SCM34PT	SCM35PT	SCM36PT	UNITS
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	40	50	60	Volts
Maximum RMS Voltage	V _{RMS}	14	21	28	35	42	Volts
Maximum DC Blocking Voltage	V _D C	20	30	40	50	60	Volts
Maximum Average Forward Rectified Current at TL (SEE FIG.1)(Note 3)	I _O			3.0			Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	I _{FSM}			100			Amps
Typical Junction Capacitance (Note 2)	C _J			250			pF
Typical Thermal Resistance (Note 3)	R _θ _{JL}			15			°C / W
Operating Temperature Range	T _J		-65 to +125		-65 to +150		°C
Storage Temperature Range	T _{STG}			-65 to +150			°C

ELECTRICAL CHARACTERISTICS (At TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	SCM32PT	SCM33PT	SCM34PT	SCM35PT	SCM36PT	UNITS
Maximum Instantaneous Forward Voltage at 3.0 A DC (Note 1)	V _F		0.55		0.70		Volts
Maximum Average Reverse Current (Note 1)	@ TA = 25°C @ TA = 100°C	IR		0.5			mAmps
at Rated DC Blocking Voltage			20		10		mAmps

NOTES : 1. Pulse test : 300 us pulse width, 1% duty cycle
 2. Measured at 1.0 MHz and applied reverse voltage of 4.0 volts
 3. P.C.B. mounted 0.31 x 0.31" (8 x 8mm) copper pad areas

2002-5

RATING CHARACTERISTIC CURVES (SCM32PT THRU SCM36PT)

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS




FIG. 2 - INSTANTANEOUS FORWARD CURRENT, (A)




FIG. 4 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 5 - TYPICAL JUNCTION CAPACITANCE

