



# VRLA Rechargeable Battery

## BPS5-6



### FEATURES

- Maintenance Free ( topping up not needed )
- Non - spillable ( no free electrolyte )
- Low Self Discharge, less than 3% per month
- both Vertical & Horizontal installations

### APPLICATIONS

- UPS
- Security Systems
- Medical Equipment
- Laboratory Equipment
- Power Packs
- Emergency Lighting
- R/C Cars & Planes



### SPECIFICATIONS

Nominal Voltage	6 V
Nominal Capacity	5.0Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	950g(2.09lbs.)
Terminals	T1 (Faston Tab 187) T2 is optional
Internal Resistance	≤ 13.5mΩ (Fully Charged )
Max. Discharge Current	75 A (5 sec.)
Max. Charge Current	1.50 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS( UL 94-HB) BPS5-6 Optional: Flame Retardant ABS(UL 94-V0) BPS5-6FR

- IEC 61056-1
- JIS C 8702-1
- GB/T 19639.1

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<p>■ <b>Length</b> 70±1.5 (2.76±0.06)</p> <p>■ <b>Width</b> 48±1.5 (1.89±0.06)</p> <p>■ <b>Container Height</b> 102±1.5 (4.02±0.06)</p> <p>■ <b>Total Height</b> 107±2.0 (4.21±0.08)</p>		<p>● Terminal T1</p> <p>● Terminal T2</p>

### Constant power discharge characteristics at 25 °C/77 °F Unit: W

Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	90.4	66.5	53.3	31.7	18.20	7.29	5.02	2.808	1.478
1.75V	104.6	72.1	55.8	32.9	18.74	7.43	5.10	2.850	1.500
1.70V	111.2	74.7	57.5	33.7	19.08	7.50	5.13	2.864	1.506
1.65V	116.2	76.5	58.8	34.2	19.31	7.55	5.15	2.873	1.512
1.60V	120.0	78.0	60.0	34.5	19.50	7.60	5.16	2.873	1.512

### Constant current discharge characteristics at 25 °C/77 °F Unit: A

Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	16.29	11.71	9.27	5.38	3.06	1.21	0.837	0.468	0.246
1.75V	19.20	12.69	9.70	5.58	3.15	1.24	0.850	0.475	0.250
1.70V	20.40	13.15	10.00	5.71	3.21	1.25	0.855	0.477	0.251
1.65V	21.31	13.46	10.23	5.79	3.24	1.26	0.858	0.479	0.252
1.60V	22.02	13.73	10.43	5.85	3.28	1.27	0.860	0.479	0.252

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.

For operation, please refer to the instruction from technical manual.