
Spec Sheet

SMD Power Inductors (NS series)

NS12565T100MN



Features

- Item Summary
 10 μH(±20%), 6.96A, 4.75A
- Lifecycle Stage

Mass Production

- Standard packaging quantity (minimum)

Taping 2000pcs(500pcs*4reel)


Products characteristics table

| CaseSize (EIA/JIS) | -/125125 |
|---|--------------|
| Inductance | 10 μ H(±20%) |
| Inductance Measuring Frequency | 100kHz |
| Rated Current -Saturation Current | 6.96A |
| Rated Current -Temperature Rise Current | 4.75A |
| DC Resistance (max) | 0.02388Ω |
| Avg. of DC.Resistance | 0.0199Ω |
| Self-resonant Frequency (min) | 15.8MHz |
| RoHS Compliance | Yes |
| Halogen Free | Yes |
| Soldering Method | Reflow |

External Dimensions

| L | 12.5mm ±0.3 |
|---|-------------|
| W | 12.5mm ±0.3 |
| Н | 6.5mm ±0.35 |


Recommended Land Patterns



2015.03.09

SMD Power Inductors (NS series)

NS12565T100MN



Dimension unit: mm unit: inch

Length: 12.5 +/- 0.3 (0.492 +/- 0.012)

Width: 12.5 +/- 0.3 (0.492 +/- 0.012)

Height: 6.5 +/- 0.35 (0.256 +/- 0.014)

Inductance: 10 uH (test freq at 0.1MHz)

DC Resistance: 0.0199 / 0.02388 ohm (typ / max)

Saturation Current: 6.96 A (max) Temp. rise Current: 4.75 A (max)

Saturation current typical: 30% reduction from initial L value.

Temp rise Current typical: Temperature will rise by 40 deg C

