

51

5,08 U

Direct connectors for insert cards, pitch 2.5/2.54/5.0/ 5.08 mm



Socket board for direct mating, with solder eyes




---

State: Phasing out

---

51

5,08 U



#### Environmental conditions

Temperature range -25 °C/+100 °C

#### Materials

Insulating body PPO  
Contact spring CuSn, pre-nickel and tin-plated

#### Mechanical data

Mating with Leiterplatte 1,5 ± 0,14 mm

#### Electrical data (at T<sub>amb</sub> 20 °C)

Contact resistance ≤ 3 mΩ  
Rated current 5 A  
Rated voltage 250 V AC  
Rated impulse voltage ≥ 3,0 kV

#### Associated products

##### Accessories

☞ F ☞ FD ☞ FF  
☞ FL ☞ SP 3

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
5,08 U 03	3	200	2000
5,08 U 04	4	200	2000
5,08 U 05	5	200	2000
5,08 U 06	6	200	2000
5,08 U 07	7	200	2000
5,08 U 08	8	200	2000
5,08 U 09	9	200	2000
5,08 U 10	10	200	2000
5,08 U 11	11	200	2000
5,08 U 12	12	200	2000
5,08 U 13	13	200	2000
5,08 U 14	14	200	2000
5,08 U 15	15	200	2000
5,08 U 16	16	200	2000
5,08 U 17	17	200	2000
5,08 U 18	18	200	2000
5,08 U 19	19	200	2000
5,08 U 20	20	200	2000
5,08 U 21	21	200	2000
5,08 U 22	22	200	2000
5,08 U 23	23	200	2000
5,08 U 24	24	200	2000
5,08 U 25	25	200	2000
5,08 U 26	26	200	2000
5,08 U 27	27	200	2000
5,08 U 28	28	200	2000
5,08 U 29	29	200	2000
5,08 U 30	30	200	2000
5,08 U 31	31	200	2000
5,08 U 32	32	200	2000
5,08 U 33	33	200	2000

**Packaging:**

in bulk, in a cardboard box