

HWS150A-15/MEA



<b>Sales Region</b>	Worldwide
<b>Series</b>	HWS-A/ME
<b>Status</b>	Production
<b>Feature</b>	<b>Medical</b> for Medical instruments
<b>Option</b>	With cover type Approved by safety standards for medical equipment
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	89% Typ.
Rated Output Voltage[DC]	15V
Output Voltage Range[DC]	12 to 18V
Maximum Output Current	10A
Maximum Output Power	150W

### Cases Shape & Size

Case'□ shape	Unit
Width(W)	42mm Nom.
Height(H)	82mm Nom.
Depth(D)	160mm Nom.
Weight	520g Typ.

### Other

Operating Temp. Range	-10 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	ES60601-1 EN60601-1 CSA-C22.2 No.60101-1

Safety Standard(Conformed)

Remarks: This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.