

TOSHIBA CMOS DIGITAL INTEGRATED CIRCUIT SILICON MONOLITHIC

**TC74VHC367F, TC74VHC367FN, TC74VHC367FT
TC74VHC368F, TC74VHC368FN, TC74VHC368FT**

HEX BUS BUFFER
TC74VHC367 F / FN / FT NON - INVERTED, 3 - STATE OUTPUTS
TC74VHC368 F / FN / FT INVERTED, 3 - STATE OUTPUTS

(Note) The JEDEC SOP (FN) is not available in Japan.

The TC74VHC367 and 368 are advanced high speed CMOS HEX BUS BUFFERS fabricated with silicon gate C2MOS technology.

They achieve the high speed operation similar to equivalent Bipolar Schottky TTL while maintaining the CMOS low power dissipation.

They contain six buffers ; four buffers are controlled by an enable input ($\bar{G}1$), and the other two buffers are controlled by another enable input ($\bar{G}2$). The outputs of each buffer group are enabled when $\bar{G}1$ and/or $\bar{G}2$ inputs are held low ; if held high, these outputs are in a high impedance state.

The TC74VHC367 is a non - inverting output type, while the TC74VHC368 is an inverting output type.

An input protection circuit ensures that 0 to 5.5V can be applied to the input pins without regard to the supply voltage. This device can be used to interface 5V to 3V systems and two supply systems such as battery back up. This circuit prevents device destruction due to mismatched supply and input voltages.

FEATURES :


- High Speed..... $t_{pd} = 3.8\text{ns}(\text{typ.})$ at $V_{CC} = 5\text{V}$
- Low Power Dissipation..... $I_{CC} = 4\mu\text{A}(\text{Max.})$ at $T_a = 25^\circ\text{C}$
- High Noise Immunity..... $V_{NIH} = V_{NIL} = 28\% V_{CC}$ (Min.)
- Power Down Protection is provided on all inputs.
- Balanced Propagation Delays..... $t_{pLH} \approx t_{pHL}$
- Wide Operating Voltage Range.... $V_{CC} (\text{opr}) = 2\text{V} \sim 5.5\text{V}$
- Low Noise $V_{OLP} = 0.8\text{V}$ (Max.)
- Pin and Function Compatible with 74ALS367/368

TRUTH TABLE

INPUTS		OUTPUTS	
\bar{G}	A	$Y(367)$	$Y(368)$
L	L	L	H
L	H	H	L
H	X	Z	Z


X : Don't Care

Z : High Impedance





F (SOP16-P-300-1.27)
Weight : 0.18g (Typ.)


FN (SOL16-P-150-1.27)
Weight : 0.13g (Typ.)



FT (TSSOP16-P-0044-0.65)
Weight : 0.06g (Typ.)

PIN ASSIGNMENT

IEC LOGIC SYMBOL



ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	VALUE	UNIT
Supply Voltage Range	V_{CC}	$-0.5 \sim 7.0$	V
DC Input Voltage	V_{IN}	$-0.5 \sim 7.0$	V
DC Output Voltage	V_{OUT}	$-0.5 \sim V_{CC} + 0.5$	V
Input Diode Current	I_{IK}	-20	mA
Output Diode Current	I_{OK}	± 20	mA
DC Output Current	I_{OUT}	± 25	mA
DC V_{CC} /Ground Current	I_{CC}	± 50	mA
Power Dissipation	P_D	180	mW
Storage Temperature	T_{STG}	$-65 \sim 150$	°C

RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	VALUE	UNIT
Supply Voltage	V_{CC}	$2.0 \sim 5.5$	V
Input Voltage	V_{IN}	$0 \sim 5.5$	V
Output Voltage	V_{OUT}	$0 \sim V_{CC}$	V
Operating Temperature	T_{OPR}	$-40 \sim 85$	°C
Input Rise and Fall Time	dt/dv	$0 \sim 100 \text{ (} V_{CC} = 3.3 \pm 0.3 \text{ V) }$ $0 \sim 20 \text{ (} V_{CC} = 5 \pm 0.5 \text{ V) }$	ns / V

DC ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITION	V_{CC} (V)	Ta = 25°C			Ta = -40~85°C		UNIT
				MIN.	TYP.	MAX.	MIN.	MAX.	
High - Level Input Voltage	V_{IH}		2.0 3.0~ 5.5	1.50 $V_{CC} \times 0.7$	—	—	1.50 $V_{CC} \times 0.7$	—	V
Low - Level Input Voltage	V_{IL}		2.0 3.0~ 5.5	— —	—	0.50 $V_{CC} \times 0.3$	— —	0.50 $V_{CC} \times 0.3$	V
High - Level Output Voltage	V_{OH}	$V_{IN} = V_{IH}$ or V_{IL}	$I_{OH} = -50\mu A$	2.0 3.0 4.5	1.9 2.9 4.4	2.0 3.0 4.5	— — —	1.9 2.9 4.4	V
			$I_{OH} = -4mA$ $I_{OH} = -8mA$	3.0 4.5	2.58 3.94	— —	— —	2.48 3.80	
Low - Level Output Voltage	V_{OL}	$V_{IN} = V_{IH}$ or V_{IL}	$I_{OL} = 50\mu A$	2.0 3.0 4.5	— — —	0.0 0.0 0.0	0.1 0.1 0.1	— — —	V
			$I_{OL} = 4mA$ $I_{OL} = 8mA$	3.0 4.5	— —	— —	0.36 0.36	— —	
3 - State Output Off - State Current	I_{OZ}	$V_{IN} = V_{IH}$ or V_{IL} $V_{OUT} = V_{CC}$ or GND	5.5	—	—	± 0.25	—	± 2.50	μA
Input Leakage Current	I_{IN}	$V_{IN} = 5.5V$ or GND	0~5.5	—	—	± 0.1	—	± 1.0	
Quiescent Supply Current	I_{CC}	$V_{IN} = V_{CC}$ or GND	5.5	—	—	4.0	—	40.0	

AC ELECTRICAL CHARACTERISTICS (Input $t_r = t_f = 3\text{ns}$)

PARAMETER	SYMBOL	TEST CONDITION		$T_a = 25^\circ\text{C}$			$T_a = -40\sim85^\circ\text{C}$		UNIT
		V_{CC} (V)	CL (pF)	MIN.	TYP.	MAX.	MIN.	MAX.	
Propagation Delay Time (TC74VHC367)	t_{pLH} t_{pHL}	3.3 ± 0.3 5.0 ± 0.5	15	—	5.9	8.3	1.0	10.0	ns
			50	—	8.4	11.8	1.0	13.5	
			15	—	4.1	5.9	1.0	7.0	
			50	—	5.6	7.9	1.0	9.0	
Propagation Delay Time (TC74VHC368)	t_{pLH} t_{pHL}	3.3 ± 0.3 5.0 ± 0.5	15	—	5.3	7.5	1.0	9.0	ns
			50	—	7.8	11.0	1.0	12.5	
			15	—	3.8	5.5	1.0	6.5	
			50	—	5.3	7.5	1.0	8.5	
3-State Output Enable Time	t_{pZL} t_{pZH}	3.3 ± 0.3 5.0 ± 0.5	15	—	6.8	10.5	1.0	12.5	ns
			50	—	9.3	14.0	1.0	16.0	
			15	—	4.8	7.2	1.0	8.5	
			50	—	6.3	9.2	1.0	10.5	
3-State Output Disable Time	t_{pLZ} t_{pHZ}	3.3 ± 0.3 5.0 ± 0.5	50	—	9.9	13.6	1.0	15.5	pF
			50	—	6.3	9.2	1.0	10.5	
Output to Output Skew	t_{osLH} t_{osHL}	3.3 ± 0.3 5.0 ± 0.5	50	—	—	1.5	—	1.5	pF
			50	—	—	1.0	—	1.0	
Input Capacitance	C_{IN}			—	4	10	—	10	pF
Output Capacitance	C_{OUT}			—	6	—	—	—	
Power Dissipation Capacitance	C_{PD}	(Note 2)		—	19	—	—	—	

Note (1) Parameter guaranteed by design. $t_{osLH} = |t_{pLHm} - t_{pLHn}|$, $t_{osHL} = |t_{pHLM} - t_{pHLn}|$


Note (2) C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load.

Average operating current can be obtained by the equation :

$$I_{CC(\text{opr.})} = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}/6 \text{ (per bit)}$$


NOISE CHARACTERISTICS (Input $t_r = t_f = 3\text{ns}$)

PARAMETER	SYMBOL	TEST CONDITION		$T_a = 25^\circ\text{C}$			UNIT
		V_{CC} (V)		TYP.	MAX.		
Quiet Output Maximum Dynamic V_{OL}	V_{OLP}	$C_L = 50\text{pF}$	5.0	0.4	0.8	V	
Quiet Output Minimum Dynamic V_{OL}	V_{OLV}	$C_L = 50\text{pF}$	5.0	-0.4	-0.8	V	
Minimum High Level Dynamic Input Voltage	V_{IHD}	$C_L = 50\text{pF}$	5.0	—	3.5	V	
Maximum Low Level Dynamic Input Voltage	V_{ILD}	$C_L = 50\text{pF}$	5.0	—	1.5	V	

INPUT EQUIVALENT CIRCUIT

SOP 16PIN (200mil BODY) PACKAGE DIMENSIONS (SOP16-P-300-1.27)

Unit in mm




Weight : 0.18g (Typ.)

SOP 16PIN (150mil BODY) PACKAGE DIMENSIONS (SOL16-P-150-1.27)

Unit in mm


(Note) This package is not available in Japan.



Weight : 0.13g (Typ.)

TSSOP 16PIN PACKAGE DIMENSIONS (TSSOP16-P-0044-0.65)

Unit in mm



RESTRICTIONS ON PRODUCT USE

000707EBA

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.