

2N5060 THRU 2N5064

SILICON CONTROLLED RECTIFIERS
0.8 AMP, 30 THRU 200 VOLT



www.centrasemi.com

The CENTRAL SEMICONDUCTOR 2N5060 series devices are epoxy molded SCRs designed for control systems and sensing circuit applications.



TO-92 CASE

MARKING: FULL PART NUMBER

MAXIMUM RATINGS: ($T_A=25^\circ\text{C}$ unless otherwise noted)

	SYMBOL	2N5060	2N5061	2N5062	2N5063	2N5064	UNITS
Peak Repetitive Off-State Voltage	V_{DRM}, V_{RRM}	30	60	100	150	200	V
RMS On-State Current (Note 1; $T_C=80^\circ\text{C}$)	$I_T(\text{RMS})$			0.8			A
Average On-State Current (Note 1; $T_C=67^\circ\text{C}$)	$I_T(\text{AV})$			0.51			A
Average On-State Current (Note 1; $T_C=102^\circ\text{C}$)	$I_T(\text{AV})$			0.255			A
Peak One Cycle Surge Current (60Hz)	I_{TSM}			10			A
I^2t Value for Fusing ($t=8.3\text{ms}$)	I^2t			0.4			A^2s
Peak Forward Gate Power ($t_p \leq 1.0\mu\text{s}$)	P_{GM}			0.1			W
Average Forward Gate Power ($t=8.3\text{ms}$)	$P_{G(\text{AV})}$			0.01			W
Peak Forward Gate Current ($t_p \leq 1.0\mu\text{s}$)	I_{GM}			1.0			A
Peak Reverse Gate Voltage ($t_p \leq 1.0\mu\text{s}$)	V_{RGM}			5.0			V
Operating Junction Temperature	T_J			-40 to +125			$^\circ\text{C}$
Storage Temperature	T_{stg}			-40 to +150			$^\circ\text{C}$
Thermal Resistance (Note 2)	θ_{JC}			75			$^\circ\text{C/W}$
Thermal Resistance	θ_{JA}			200			$^\circ\text{C/W}$

Notes: 1) 180° Conduction Angles

2) Measured with the "flat side down" on a heatsink and held in position by a metal clamp over the curved surface.

ELECTRICAL CHARACTERISTICS: ($T_C=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I_{DRM}, I_{RRM}	V_D =Rated V_{DRM} , $R_{GK}=1.0\text{k}\Omega$			10	μA
I_{DRM}, I_{RRM}	V_D =Rated V_{DRM} , $R_{GK}=1.0\text{k}\Omega$, $T_C=110^\circ\text{C}$			50	μA
I_{GT}	$V_D=7.0\text{V}$, $R_L=100\Omega$			200	μA
I_{GT}	$V_D=7.0\text{V}$, $R_L=100\Omega$, $T_C=-40^\circ\text{C}$			350	μA
I_H	Initiating Current, $I_T=20\text{mA}$, $R_{GK}=1.0\text{k}\Omega$			5.0	mA
I_H	Initiating Current, $I_T=20\text{mA}$, $R_{GK}=1.0\text{k}\Omega$, $T_C=-40^\circ\text{C}$			10	mA
V_{GT}	$V_D=7.0\text{V}$, $R_L=100\Omega$			0.8	V
V_{GT}	$V_D=7.0\text{V}$, $R_L=100\Omega$, $T_C=-40^\circ\text{C}$			1.2	V
V_{GD}	V_D =Rated V_{DRM} , $R_L=100\Omega$, $T_C=110^\circ\text{C}$	0.1			V
V_{TM}	$I_{TM}=1.2\text{A}$, $T_A=25^\circ\text{C}$			1.7	V
dv/dt	V_D =Rated V_{DRM} , $R_{GK}=1.0\text{k}\Omega$		30		$\text{V}/\mu\text{s}$

R5 (7-May 2015)


2N5060 THRU 2N5064
SILICON CONTROLLED RECTIFIERS
0.8 AMP, 30 THRU 200 VOLT



ELECTRICAL CHARACTERISTICS - Continued: ($T_C=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	2N5060	2N5062	UNITS
		2N5061	2N5063 2N5064	
		TYP	TYP	
t_d	[V_D =Rated V_{DRM} , $I_{GT}=1.0\text{mA}$, Forward Current=1.0A, $di/dt=6.0\text{A}/\mu\text{s}$]	3.0	3.0	μs
t_r		0.2	0.2	μs
t_q	[Forward Current=1.0A, $t_p=50\mu\text{s}$, 0.1% Duty Cycle, $di/dt=6.0\text{A}/\mu\text{s}$, $dv/dt=20\text{V}/\mu\text{s}$, $I_{GT}=1.0\text{mA}$]	10	30	μs

TO-92 CASE - MECHANICAL OUTLINE



SYMBOL	DIMENSIONS			
	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A (DIA)	0.175	0.205	4.45	5.21
B	0.170	0.210	4.32	5.33
C	0.500	-	12.70	-
D	0.016	0.022	0.41	0.56
E	0.100		2.54	
F	0.050		1.27	
G	0.125	0.165	3.18	4.19
H	0.080	0.105	2.03	2.67
I	0.015		0.38	

TO-92 (REV: R1)

LEAD CODE:

- 1) Cathode
- 2) Gate
- 3) Anode

MARKING:
FULL PART NUMBER

R1

R5 (7-May 2015)

2N5060 THRU 2N5064
SILICON CONTROLLED RECTIFIERS
0.8 AMP, 30 THRU 200 VOLT



SERVICES

- Bonded Inventory
- Custom Electrical Screening
- Custom Electrical Characteristic Curves
- SPICE Models
- Custom Packaging
- Package Base Options
- Custom Device Development/ Multi Discrete Modules (MDM™)
- Bare Die Available for Hybrid Applications

LIMITATIONS AND DAMAGES DISCLAIMER: In no event shall Central be liable for any collateral, indirect, punitive, incidental, consequential, or exemplary damages in connection with or arising out of a purchase order or contract or the use of products provided hereunder, regardless of whether Central has been advised of the possibility of such damages. Excluded damages shall include, but not be restricted to: cost of removal or reinstallation, rework, ancillary costs to the procurement of substitute products, loss of profits, loss of savings, loss of use, loss of data, or business interruption. No claim, suit, or action shall be brought against Central more than two (2) years after the related cause of action has occurred.

In no event shall Central's aggregate liability from any warranty, indemnity, or other obligation arising out of or in connection with a purchase order or contract, or any use of any Central product provided hereunder, exceed the total amount paid to Central for the specific products sold under a purchase order or contract with respect to which losses or damages are claimed. The existence of more than one (1) claim against the specific products sold to Buyer under a purchase order or contract shall not enlarge or extend this limit.

Buyer understands and agrees that the foregoing liability limitations are essential elements of a purchase order or contract and that in the absence of such limitations, the material and economic terms of the purchase order or contract would be substantially different.

R5 (7-May 2015)