

**2SC5503**

## VHF to UHF Low-Noise Wide-Band Amplifier Applications


### Features

- Low noise :  $NF=1.2\text{dB typ (}f=1\text{GHz)}$ .
- High gain :  $|S_{21e}|^2=15\text{dB typ (}f=1\text{GHz)}$ .
- High cutoff frequency :  $f_T=9.0\text{GHz typ}$ .

### Package Dimensions

unit:mm

2161



### Specifications

#### Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	$V_{CBO}$		16	V
Collector-to-Emitter Voltage	$V_{CEO}$		8	V
Emitter-to-Base Voltage	$V_{EBO}$		1.5	V
Collector Current	$I_C$		50	mA
Collector Dissipation	$P_C$	Mounted on a ceramic board (250mm <sup>2</sup> ×0.8mm)	400	mW
Junction Temperature	$T_J$		150	°C
Storage Temperature	$T_{stg}$		-55 to +150	°C

#### Electrical Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector Cutoff Current	$I_{CBO}$	$V_{CB}=10\text{V}, I_E=0$			1.0	$\mu\text{A}$
Emitter Cutoff Current	$I_{EBO}$	$V_{EB}=1\text{V}, I_C=0$			10	$\mu\text{A}$
DC Current Gain	$h_{FE}$	$V_{CE}=5\text{V}, I_C=15\text{mA}$	90*		270*	
Gain-Bandwidth Product	$f_T$	$V_{CE}=5\text{V}, I_C=15\text{mA}$		9.0		GHz
Output Capacitance	$C_{ob}$	$V_{CB}=10\text{V}, f=1\text{MHz}$		0.6	1.1	pF
Reverse Transfer Capacitance	$C_{re}$	$V_{CB}=10\text{V}, f=1\text{MHz}$		0.3		pF

\* : The 2SC5503 is classified by 15mA  $h_{FE}$  as follows :

Continued on next page.

Marking	GN	
Rank	4	5
$h_{FE}$	90 to 180	135 to 270

■ Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.

■ SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO products described or contained herein.







**SANYO Electric Co.,Ltd. Semiconductor Company**

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN


# 2SC5503

Continued from preceding page.

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Forward Transfer Gain	$ S_{21e} ^2$	$V_{CE}=5V, I_C=15mA, f=1GHz$	12	15		dB
Noise Figure	NF	$V_{CE}=5V, I_C=5mA, f=1GHz$		1.2	2.5	dB



## 2SC5503



### S Parameters (Common emitter)

$V_{CE}=2V, I_C=1mA, Z_O=50\Omega$

Freq (MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.978	-11.2	2.735	166.9	0.030	81.5	0.990	-6.0
200	0.950	-24.0	2.456	155.8	0.059	72.5	0.967	-12.4
400	0.912	-44.5	2.225	137.6	0.108	57.7	0.896	-24.9
600	0.845	-66.6	2.181	121.0	0.134	45.6	0.840	-31.8
800	0.763	-89.1	2.297	105.2	0.156	35.6	0.783	-38.8
1000	0.745	-102.3	1.813	93.4	0.170	29.5	0.707	-45.4
1200	0.672	-121.1	1.837	81.0	0.174	23.0	0.687	-49.9
1400	0.638	-135.1	1.641	70.1	0.171	20.2	0.682	-53.4
1600	0.601	-148.7	1.514	61.3	0.165	19.4	0.670	-57.8
1800	0.578	-160.5	1.284	52.0	0.168	15.1	0.655	-61.9
2000	0.569	-171.0	1.286	43.6	0.162	17.9	0.626	-66.2

$V_{CE}=2V, I_C=5mA, Z_O=50\Omega$

Freq (MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.867	-24.3	10.957	156.6	0.028	73.8	0.933	-15.9
200	0.783	-45.5	9.406	140.8	0.048	62.3	0.812	-29.1
400	0.622	-84.4	7.739	116.6	0.071	50.6	0.610	-43.1
600	0.504	-113.8	6.123	99.4	0.086	47.0	0.508	-48.5
800	0.441	-135.3	4.951	87.5	0.098	46.0	0.446	-51.8
1000	0.402	-151.6	4.086	77.6	0.110	46.9	0.405	-54.9
1200	0.377	-165.8	3.524	69.2	0.123	46.6	0.393	-57.6
1400	0.368	-175.7	3.026	61.8	0.135	46.6	0.389	-60.9
1600	0.362	175.3	2.672	56.0	0.151	45.5	0.382	-63.8
1800	0.353	164.8	2.427	49.0	0.165	44.8	0.379	-67.6
2000	0.351	156.6	2.206	42.8	0.182	44.5	0.383	-71.0

## 2SC5503

$V_{CE}=2V, I_C=10mA, Z_0=50\Omega$

Freq (MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.745	-37.2	18.245	149.0	0.025	68.9	0.858	-24.0
200	0.612	-70.0	15.211	128.7	0.041	59.0	0.674	-38.0
400	0.455	-113.3	10.170	104.5	0.057	54.1	0.465	-48.1
600	0.384	-140.0	7.289	90.5	0.073	55.3	0.381	-51.2
800	0.359	-157.0	5.621	81.3	0.088	55.9	0.338	-53.2
1000	0.345	-169.2	4.530	73.4	0.105	55.8	0.316	-55.4
1200	0.336	179.5	3.855	66.3	0.122	54.9	0.308	-58.4
1400	0.330	170.2	3.306	59.7	0.139	54.1	0.306	-62.0
1600	0.328	162.3	2.928	54.2	0.156	52.2	0.311	-65.1
1800	0.328	154.2	2.637	48.1	0.175	50.6	0.310	-68.9
2000	0.328	146.7	2.380	42.4	0.193	48.7	0.316	-72.6

$V_{CE}=2V, I_C=15mA, Z_0=50\Omega$

Freq (MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.643	-50.0	23.482	143.0	0.022	67.2	0.804	-28.7
200	0.508	-88.2	17.997	120.8	0.036	59.3	0.590	-42.0
400	0.390	-131.0	10.891	98.7	0.052	59.1	0.398	-48.9
600	0.356	-152.1	7.550	87.3	0.068	59.7	0.327	-50.4
800	0.343	-166.9	5.766	78.9	0.086	60.3	0.298	-52.1
1000	0.335	-178.2	4.650	71.4	0.104	59.8	0.283	-54.7
1200	0.330	172.4	3.934	64.9	0.122	58.5	0.281	-57.8
1400	0.327	164.4	3.364	58.7	0.140	57.2	0.279	-61.5
1600	0.325	157.1	2.982	53.4	0.159	55.0	0.284	-64.8
1800	0.328	149.2	2.683	47.5	0.178	52.8	0.289	-68.9
2000	0.327	142.5	2.426	41.9	0.197	50.3	0.294	-72.6

$V_{CE}=5V, I_C=1mA, Z_0=50\Omega$

Freq (MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.975	-11.0	2.523	168.1	0.024	81.1	0.994	-5.4
200	0.962	-21.2	2.045	158.4	0.047	74.1	0.976	-10.3
400	0.927	-41.1	2.215	140.2	0.088	60.0	0.925	-20.3
600	0.855	-62.8	2.270	123.7	0.116	49.2	0.892	-25.9
800	0.803	-80.8	2.055	110.3	0.130	39.3	0.831	-33.1
1000	0.765	-97.0	1.853	97.5	0.142	32.9	0.772	-38.4
1200	0.690	-115.2	1.867	85.0	0.140	28.2	0.728	-43.5
1400	0.615	-132.6	1.851	73.4	0.143	25.1	0.729	-46.8
1600	0.600	-144.0	1.624	64.9	0.146	21.2	0.754	-50.2
1800	0.582	-155.5	1.503	55.5	0.142	20.9	0.702	-54.6
2000	0.527	-169.9	1.390	47.0	0.139	23.9	0.718	-58.0

## 2SC5503

$V_{CE}=5V, I_C=5mA, Z_O=50\Omega$

Freq (MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.881	-21.7	10.542	158.6	0.023	76.3	0.947	-13.4
200	0.806	-40.6	9.637	142.8	0.040	64.6	0.839	-24.0
400	0.638	-76.7	8.085	119.3	0.061	53.2	0.681	-34.6
600	0.521	-102.7	6.372	103.0	0.074	49.4	0.573	-39.2
800	0.436	-124.9	5.262	90.4	0.085	48.4	0.513	-42.0
1000	0.381	-142.5	4.419	79.8	0.095	50.2	0.487	-44.2
1200	0.357	-156.0	3.792	71.7	0.107	49.6	0.472	-46.7
1400	0.338	-167.4	3.253	64.1	0.119	49.4	0.464	-49.7
1600	0.335	-176.3	2.859	58.4	0.131	49.5	0.461	-52.4
1800	0.316	171.2	2.634	51.3	0.145	49.4	0.466	-55.7
2000	0.316	162.6	2.377	45.0	0.160	48.8	0.467	-58.9

$V_{CE}=5V, I_C=10mA, Z_O=50\Omega$

Freq (MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.776	-32.1	18.500	151.2	0.020	70.4	0.890	-19.1
200	0.638	-61.2	15.777	131.6	0.034	62.6	0.732	-30.0
400	0.451	-102.4	10.900	107.1	0.050	56.7	0.538	-37.8
600	0.360	-129.3	7.927	92.7	0.063	57.6	0.459	-39.4
800	0.325	-147.1	6.112	83.4	0.076	58.4	0.422	-40.9
1000	0.305	-160.4	4.949	75.3	0.091	58.3	0.402	-42.7
1200	0.293	-172.0	4.188	68.4	0.106	57.9	0.397	-45.2
1400	0.285	177.7	3.600	61.6	0.120	57.4	0.393	-48.3
1600	0.280	168.6	3.191	56.3	0.137	56.2	0.398	-51.4
1800	0.281	160.3	2.881	50.3	0.153	54.4	0.399	-54.8
2000	0.280	152.0	2.607	44.4	0.169	52.8	0.404	-58.3

$V_{CE}=5V, I_C=15mA, Z_O=50\Omega$

Freq (MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.683	-41.4	24.196	145.9	0.019	70.5	0.843	-22.7
200	0.524	-76.6	19.160	123.9	0.030	61.6	0.654	-32.9
400	0.373	-117.4	11.820	101.5	0.045	60.4	0.479	-37.3
600	0.318	-141.2	8.273	89.3	0.059	61.7	0.416	-37.9
800	0.296	-157.5	6.341	80.9	0.074	62.2	0.388	-39.0
1000	0.284	-169.6	5.112	73.4	0.090	61.9	0.377	-41.0
1200	0.278	179.7	4.321	66.9	0.106	61.2	0.374	-43.8
1400	0.274	170.7	3.700	60.5	0.122	59.8	0.372	-47.1
1600	0.272	162.7	3.271	55.4	0.138	58.6	0.379	-50.3
1800	0.273	154.4	2.952	49.6	0.156	56.3	0.382	-53.8
2000	0.273	147.1	2.671	44.0	0.173	54.4	0.387	-57.6

- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of October, 1999. Specifications and information herein are subject to change without notice.