

SANYO	No.1637B	2SC3638
NPN Triple Diffused Planar Silicon Transistor VERY HIGH-DEFINITION DISPLAY HORIZONTAL DEFLECTION OUTPUT APPLICATIONS		

Features

- . High reliability (Adoption of HVP process)
- . Fast speed.
- . High breakdown voltage.
- . Adoption of MBIT process.


Absolute Maximum Ratings at Ta=25°C

			unit
Collector-to-Base Voltage	V _{CB0}	900	V
Collector-to-Emitter Voltage	V _{CE0}	500	V
Emitter-to-Base Voltage	V _{EBO}	7	V
Collector Current	I _C	15	A
Peak Collector Current	i _{cp}	25	A
Collector Dissipation	P _C	100	W
Junction Temperature	T _j	150	°C
Storage Temperature	T _{stg}	-55 to +150	°C


Electrical Characteristics at Ta=25°C









			min	typ	max	
Collector Cutoff Current	I _{CB0}	V _{CB} =500V, I _E =0			10	μA
	I _{CES}	V _{CE} =900V, R _{BE} =0			0.5	mA
Collector-to-Emitter Sustain Voltage	V _{CEO(sus)}	I _C =100mA, I _B =0	500			V
Emitter Cutoff Current	I _{EBO}	V _{EB} =5V, I _C =0			1	mA
Collector-to-Emitter Saturation Voltage	V _{CE(sat)}	I _C =7V, I _B =1.4A			2	V
Base-to-Emitter Saturation Voltage	V _{BE(sat)}	I _C =7A, I _B =1.4A			1.5	V
DC Current Gain	h _{FE}	V _{CE} =5V, I _C =1.4A	8			
Storage Time	t _{stg}	I _C =7A, I _{B1} =1.4A, I _{B2} =-2.8A			3.0	μs
Fall Time	t _f	I _C =7A, I _{B1} =1.4A, I _{B2} =-2.8A	0.1	0.2		μs




Switching Time Test Circuit



Package Dimensions 2022
(unit: mm)







- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.