

FGW15N40A

Strobe Flash N-Channel Logic Level IGBT

Features

- $V_{CE(SAT)} = 4.4V$ at $I_C = 150A$
- $t_{fl} = 1.1\mu s$, $t_{d(OFF)} = 0.46\mu s$
- 2kV ESD Protected
- High Peak Current Density
- TSSOP - 8 package, small footprint, low profile (1mm thick)


Applications

- Camera Strobe


General Description

This N-Channel IGBT is a MOS gated, logic level device which has been especially tailored for camera flash applications where board space is a premium. These devices have been designed to offer exceptional power dissipation in a very small footprint for applications where bigger, more expensive packages are impractical. The gate is ESD protected with a zener diode.

FGW15N40A Strobe Flash N-Channel Logic Level IGBT



Internal Diagram



Device Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Ratings	Units
BV_{CES}	Collector to Emitter Breakdown Voltage	400	V
I_C	Collector Current Continuous(DC)	8	A
I_{CP}	Collector Current Pulsed(100 μ s)	150	A
V_{GES}	Gate to Emitter Voltage Continuous(DC)	± 6	V
V_{GEP}	Gate to Emitter Voltage Pulsed	± 8	V
P_D	Power Dissipation Total $T_C = 25^\circ\text{C}$	1.25	W
T_J	Operating Junction Temperature Range	-40 to 150	$^\circ\text{C}$
T_{STG}	Storage Junction Temperature Range	-40 to 150	$^\circ\text{C}$
ESD	Electrostatic Discharge Voltage at 100pF, 1500 Ω	2	kV

Package Marking and Ordering Information

Device Marking	Device	Package	Tape Width	Quantity
15N40A	FGW15N40A	TSSOP - 8	12mm / 16mm	2500

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
--------	-----------	-----------------	-----	-----	-----	-------

Off State Characteristics

BV_{CES}	Collector to Emitter Breakdown Voltage	$I_C = 1\text{mA}, V_{GE} = 0\text{V}$	400	-	-	V	
BV_{GES}	Gate-Emitter Breakdown Voltage	$I_{GES} = \pm 1\text{mA}$	± 8	-	-	V	
I_{CES}	Collector to Emitter Leakage Current	$V_{CE} = 400\text{V}$	$T_C = +25^\circ\text{C}$	-	-	10	μA
			$T_C = +125^\circ\text{C}$	-	-	250	μA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE} = \pm 8\text{V}$	-	-	± 10	μA	

On State Characteristics

$V_{CE(SAT)}$	Collector to Emitter Saturation Voltage	$I_C = 150\text{A}, V_{GE} = 4.0\text{V}$ (NOTE 1)	-	4.4	6.0	V
---------------	---	--	---	-----	-----	---

Dynamic Characteristics

$Q_{G(ON)}$	Gate Charge	$I_C = 150\text{A}, V_{CE} = 300\text{V}, V_{GE} = 8\text{V}$	-	41	-	nC
V_{GEPL}	Gate to Emitter Plateau Voltage	$I_C = 150\text{A}, V_{CE} = 300\text{V}$	-	3.3	-	V
$V_{GE(TH)}$	Gate to Emitter Threshold Voltage	$I_C = 1.0\text{mA}, V_{CE} = V_{GE}$	0.4	0.61	0.75	V
C_{IES}	Input Capacitance	$V_{CE} = 10\text{V}, V_{GE} = 0\text{V}, f = 1\text{MHz}$	-	1800	-	pF

Switching Characteristics

t_{ON}	Turn-On Time	$V_{CE} = 300\text{V}, I_C = 150\text{A},$ $V_{GE} = 4\text{V}, R_L = 2\Omega,$ $R_G = 51\Omega, T_J = 25^\circ\text{C}$	-	0.91	-	μs
$t_{d(ON)I}$	Current Turn-On Delay Time		-	0.18	-	μs
t_{rI}	Current Rise Time		-	0.73	-	μs
t_{OFF}	Turn-Off Time		-	1.56	-	μs
$t_{d(OFF)I}$	Current Turn-Off Delay Time		-	0.46	-	μs
t_{fI}	Current Fall Time		-	1.1	-	μs

Thermal Characteristics

$R_{\theta JA}$	Thermal Resistance Junction-Case	TSSOP - 8 (NOTE 2)	-	80	-	$^\circ\text{C/W}$
-----------------	----------------------------------	--------------------	---	----	---	--------------------

Notes:

1. Pulse Duration = 100 μsec
2. Mounted on a 1 inch² 1oz copper pad

Typical Characteristics




Figure 1. Collector to Emitter On-State Voltage vs Collector Current




Figure 2. Collector to Emitter On-State Voltage vs Collector Current




Figure 3. Collector to Emitter On-State Voltage vs Collector Current




Figure 4. Collector to Emitter On-State Voltage vs Collector Current




Figure 5. Collector to Emitter Saturation Voltage vs Case Temperature




Figure 6. Collector to Emitter Saturation Voltage vs Case Temperature

Typical Characteristics (Continued)




Figure 7. Collector to Emitter On-State Voltage vs Gate to Emitter Voltage




Figure 8. Collector to Emitter On-State Voltage vs Gate to Emitter Voltage




Figure 9. Collector to Emitter On-State Voltage vs Gate to Emitter Voltage




Figure 10. Collector to Emitter On-State Voltage vs Gate to Emitter Voltage




Figure 11. Gate to Emitter Threshold Voltage vs Case Temperature




Figure 12. Capacitance vs Collector to Emitter Voltage

Typical Characteristics (Continued)




Figure 13. Switching Time vs Collector Current




Figure 14. Switching Time vs Gate Resistance




Figure 15. Gate Charge




Figure 16. Collector Current Limit vs Gate to Emitter Voltage




Figure 17. Normalized Transient Thermal Impedance, Junction to Case

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE ^x TM	FACT TM	<i>i-Lo</i> TM	PACMAN TM	SPM TM
ActiveArray TM	FACT Quiet Series TM	ImpliedDisconnect TM	POP TM	Stealth TM
Bottomless TM	FAST [®]	IntelliMAX TM	Power247 TM	SuperFET TM
Build it Now TM	FAST ^r TM	ISOPLANAR TM	PowerEdge TM	SuperSOT TM -3
CoolFET TM	FPST TM	LittleFET TM	PowerSaver TM	SuperSOT TM -6
CROSSVOLT TM	FRFET TM	MICROCOUPLER TM	PowerTrench [®]	SuperSOT TM -8
DOME TM	GlobalOptoisolator TM	MicroFET TM	QFET [®]	SyncFET TM
EcoSPARK TM	GTO TM	MicroPak TM	QS TM	TinyLogic [®]
E ² C ^{MOS} TM	HiSeC TM	MICROWIRE TM	QT Optoelectronics TM	TINYOPTO TM
EnSigna TM	I ² C TM	MSX TM	Quiet Series TM	TruTranslation TM
		MSXPro TM	RapidConfigure TM	UHC TM
Across the board. Around the world. TM		OCX TM	RapidConnect TM	UltraFET [®]
The Power Franchise [®]		OCXPro TM	μSerDes TM	UniFET TM
Programmable Active Droop TM		OPTOLOGIC [®]	SILENT SWITCHER [®]	VCX TM
		OPTOPLANAR TM	SMART START TM	Wire TM

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
- A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

Rev. 116