
## BC807 / BC808

### **PNP Silicon Epitaxial Planar Transistors**

for switching, AF driver and amplifier applications

These transistors are subdivided into three groups -16, -25 and -40, according to their current gain. As complementary types the NPN transistors BC817 and BC818 are recommended.



1. Base 2. Emitter 3. Collector SOT-23 Plastic Package

#### Absolute Maximum Ratings ( $T_a = 25$ °C)

Parameter		Symbol	Value	Unit	
Collector Base Voltage	BC807 BC808	-V <sub>CBO</sub>	50 30	V	
Collector Emitter Voltage	BC807 BC808	-V <sub>CEO</sub>	45 25	V	
Emitter Base Voltage		-V <sub>EBO</sub>	5	V	
Collector Current		-I <sub>C</sub>	500	mA	
Power Dissipation		P <sub>tot</sub>	200	mW	
Thermal Resistance Junction to Ambient Air		$R_{ heta JA}$	500	K/W	
Junction Temperature		TJ	150	°C	
Storage Temperature Range		Ts	- 55 to + 150	°C	

#### Electrical Characteristics at T<sub>a</sub> = 25 °C

Parameter		Symbol	Min.	Тур.	Max.	Unit
DC Current Gain						
at -V <sub>CE</sub> = 1 V, -I <sub>C</sub> = 100 mA Current Gain Group	-16	$h_FE$	100	-	250	-
	-25	h <sub>FE</sub>	160	-	400	-
	-40	h <sub>FE</sub>	250	-	600	-
at - $V_{CE}$ = 1 V, - $I_{C}$ = 500 mA		h <sub>FE</sub>	40	-	-	-
Collector Base Cutoff Current at -V <sub>CB</sub> = 20 V		-I <sub>CBO</sub>	-	-	100	nA
Emitter-Base Cutoff Current at -V <sub>EB</sub> = 5 V		-I <sub>EBO</sub>	-	-	100	nA
Collector Saturation Voltage at $-I_C = 500 \text{ mA}$ , $-I_B = 50 \text{ mA}$		-V <sub>CEsat</sub>	ı	ı	0.7	V
Base-Emitter Voltage at $-I_C = 500$ mA, $-V_{CE} = 1$ V		-V <sub>BE(on)</sub>	1	1	1.2	V
Gain -Bandwidth Product at -V <sub>CE</sub> = 5 V, -I <sub>C</sub> = 10 mA, $f = 50$ MHz		f⊤	80	-	-	MHz
Collector-Base Capacitance at -V <sub>CB</sub> = 10 V, f = 1 MHz		ССВО	-	9	-	pF















Dated: 19/12/2006











# SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)







Dated: 19/12/2006