

RGSP12W

Fast Plastic Power Rectifiers

VOLTAGE: 1500V

CURRENT:12.0A



FEATURE

- Plastic package has Underwriters Laboratories Flammability Classification 94V-0
- Ideally suited for use in very high frequency switching power supplies, inverters and as free wheeling diodes
- Ultra fast recovery time for high efficiency
- Excellent high temperature switching
- Glass passivated junction
- High voltage and high reliability
- High speed switching
- Low forward voltage


MECHANICAL DATA

Case: JEDEC TO-220AB molded plastic body over passivated chip

Terminals: Plated axial leads, solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	RGSP12W	units
Maximum Recurrent Peak Reverse Voltage	V _{rrm}	1500	V
Maximum RMS Voltage	V _{rms}	1050	V
Maximum DC Blocking Voltage	V _{dc}	1500	V
Maximum Average Forward Rectified Current at T _c =100°C	I _{f(av)}	12.0	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I _{fsm}	110	A
Maximum Forward Voltage at Forward Current is 6.5A and 25°C	V _f	1.3	V
Maximum Reverse Recovery Time (Note 1)	T _{rr}	200	nS
Typical thermal resistance junction to case	R _{th(jc)}	3.0	°C/W
Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =125°C	I _r	250 1.0	µA mA
Storage and Operating Temperature Range	T _{stg} , T _j	-55 to +150	°C

Note:

1. Reverse Recovery Condition I_f =0.5A, I_r =1.0A, I_{rr} =0.25A




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Instantaneous Forward Characteristics




Figure 4. Typical Reverse Leakage Characteristics Per Leg




Figure 5. Typical Junction Capacitance Per Leg