

GL194A NPN SILICON PLANAR MEDIUM POWER TRANSISTOR



Description

The GL194A is designed for medium power amplifier applications.

Features

- 1 Amp continuous current
- Complementary to GL195A

Package Dimensions



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	6.70	7.30	B	13°TYP.	
C	2.90	3.10	J	2.30 REF.	
D	0.02	0.10	1	6.30	6.70
E	0°	10°	2	6.30	6.70
I	0.60	0.80	3	3.30	3.70
H	0.25	0.35	4	3.30	3.70
			5	1.40	1.80

Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Ratings	Unit
Junction Temperature	Tj	+150	°C
Storage Temperature	Tstg	-65~+150	°C
Collector to Base Voltage	VCBO	40	V
Collector to Emitter Voltage	VCEO	40	V
Emitter to Base Voltage	VEBO	5	V
Collector Current (DC)	IC	1	A
Collector Current (Pulse)	Ic	2	A
Total Power Dissipation	PD	2	W

Electrical Characteristics (Ta = 25°C, unless otherwise stated)


Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BVCBO	40	-	-	V	IC=100uA, IE=0
*BVCEO	40	-	-	V	IC=10mA, IB=0
BVEBO	5	-	-	V	IE=100uA, IC=0
ICBO	-	-	100	nA	VCB=30V, IE=0
ICES	-	-	100	nA	VCE=30V
IEBO	-	-	100	nA	VEB=4V, IC=0
*VCE(sat)1	-	-	0.3	V	IC=500mA, IB=50mA
*VCE(sat)2	-	-	0.5	V	IC=1A, IB=100mA
*VBE(sat)	-	-	1.1	V	IC=1A, IB=100mA
*VBE(on)	-	-	1.0	V	VCE=5V, IC=1A
*hFE1	300	-	-		VCE=5V, IC=1mA
*hFE2	300	-	900		VCE=5V, IC=500mA
*hFE3	200	-	-		VCE=5V, IC=1A
*hFE4	35	-	-		VCE=5V, IC=2A
fT	150	-	-	MHz	VCE=10V, IC=50mA, f=100MHz
Cob	-	-	10	pF	VCB=10V, IE=0, f=1MHz

*Measured under pulse condition. Pulse width=300μs, Duty Cycle≤2%

Classification Of hFE2

Rank	P	Q
Range	300 ~ 700	500 ~ 900

Characteristics Curve



Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165