

FEATURES AND SPECIFICATIONS

Features and Benefits

- Sizes 6 to 50 circuits
- Positive latch retains clip to dual row panel mount or headers
- Optional front polarization rib available (version B)
- Stacks single row 70066/70400D assemblies side-to-side and end-to-end to form a larger dual row connector, accepts 70450C dual row connector to provide positive latch feature

Physical

Housing: Black glass-filled polyester, UL 94V-0
 Operating Temperature: -40 to +105°C




2.54mm (.100") Pitch

SL™

Interim Clip

70013

Dual Row




Reference Information

Packaging: Bag
 UL File No.: E29179
 CSA File No.: LR19980
 Mates With: 70013, Version A—8723B and 8724B
 70013, Version B—70022, 70227 and 70229
 Designed In: Inches

2.54mm (.100") Pitch

CATALOG DRAWING (FOR REFERENCE ONLY)

Not For Use With Molex C-Grid III™ Components



ORDERING INFORMATION AND DIMENSIONS

Circuits	Order No.		Dimension
	Version A Without Ribs	Version B With Ribs	A
6	• 15-04-5061	• 15-04-5064	11.83 (.466)
8	• 15-04-5081	• 15-04-5084	14.37 (.566)
10	• 15-04-5101	• 15-04-5104	16.91 (.666)
12	• 15-04-5121	• 15-04-5124	19.45 (.766)
14	• 15-04-5141	• 15-04-5144	21.99 (.866)
16	• 15-04-5161	• 15-04-5164	24.53 (.966)
18	• 15-04-5181	• 15-04-5184	27.07 (1.066)
20	• 15-04-5201	• 15-04-5204	29.61 (1.166)
22	• 15-04-5221	• 15-04-5224	32.15 (1.266)
24	• 15-04-5241	• 15-04-5244	34.69 (1.366)
26	• 15-04-5261	• 15-04-5264	37.23 (1.466)
28	• 15-04-5281	• 15-04-5284	39.77 (1.566)

Circuits	Order No.		Dimension
	Version A Without Ribs	Version B With Ribs	A
30	• 15-04-5301	• 15-04-5304	42.31 (1.666)
32	• 15-04-5321	• 15-04-5324	44.85 (1.766)
34	• 15-04-5341	• 15-04-5344	47.39 (1.866)
36	• 15-04-5361	• 15-04-5364	49.93 (1.966)
38	• 15-04-5381	• 15-04-5384	52.47 (2.066)
40	• 15-04-5401	• 15-04-5404	55.01 (2.166)
42	• 15-04-5421	• 15-04-5424	57.55 (2.266)
44	• 15-04-5441	• 15-04-5444	60.09 (2.366)
46	• 15-04-5461	• 15-04-5464	62.63 (2.466)
48	• 15-04-5481	• 15-04-5484	65.17 (2.566)
50	• 15-04-5501	• 15-04-5504	67.71 (2.666)

• US Standard Product, available through Molex franchised distributors