

[Home](#) » [Emulators](#) » 701900

Categories

Emulators

- C2000™
- C3x/4x™
- C5000™
- C6000™
- OMAP™
- Special Hardware
- C2000™
- C3x/4x™
- C5000™
- C6000™
- OMAP™
- Development Bundles
- Evaluation Modules
- Software
- Special Hardware
- Starter Kits
- Third Party

[View All Products ->](#)

Shopping Cart

0 items

XDS510 USB JTAG Emulator



Documentation

Installation Guide
Drivers and Support

Application

Debug hardware
Debug software
Flash programming (F2812)

Warranty: 1 year from date of purchase



XDS510 USB JTAG Emulator

Hardware Features

- Supports Texas Instruments Digital Signal Processors and Microcontrollers with **JTAG** interface (F240x, F28xx, C54xx, C55xx, C6xxx, TMS470 ARM9, OMAP)
- Compatible with XDS510 from Texas Instruments
- Operates off PC/laptop USB port, **no** internal adapter required
- USB bus powered, **no** power supply required
- Supports USB 1.x and USB 2.0 (full speed)
- Advanced emulation controller provides high performance
- Compatible with +3.3V or +5V processors
- One LED provides operational status

Software Features

- Compatible with Code Composer Studio from Texas Instruments
- Supports Spectrum Digital's "SDConfig" Utility designed for emulator to target verification
- Compatible with Windows 98 SE, 2000, XP

What's Included

- XDS510 USB JTAG Emulator
- USB cable
- CD-ROM with drivers
- Setup instructions
- Warranty registration card

You May Need

- Code Composer Studio
- 4 Channel JTAG Expander
- DSP Target Board (EVM, eZdsp, DSK)