

**Micro Commercial Components** 




Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

# BAS16WT MMBD4148WT

## **Features**

- Power dissipation: 200mW (T<sub>amb</sub>=25 °C)
- Collector current:150mA



Marking: A2, KA2, KT1


# **Maximum Ratings**

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1


## Electrical Characteristics @ 25°C Unless Otherwise Specified


Reverse Voltage	$V_R$	75V	I <sub>R</sub> =100 μ A
Peak Forward	I <sub>F</sub>	150mA	
Current			
Maximum		0.715V	$I_{FM} = 1 \text{mA};$
Instantaneous	$V_{F}$	0.855	$I_{FM} = 10 \text{mA};$
Forward Voltage		1.0V	I <sub>FM</sub> =50mA;
		1.25V	I <sub>FM</sub> =150mA;
Maximum DC			
Reverse Current At	$I_R$	1.0μΑ	V <sub>R</sub> =75Volts
Rated DC Blocking		,	
Voltage			
Diode Capacitance	C <sub>D</sub>	2pF	Measured at 1.0MHz,
			V <sub>R</sub> =0V
Reverse Recovery	T <sub>rr</sub>	4ns	I <sub>F</sub> =I <sub>R</sub> =10mA
Time			Irr=0.1I <sub>R</sub>

# 200mW Switching Diode



DIMENSIONS					
	INCHES		ММ		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.071	.087	1.80	2.20	
В	.045	.053	1.15	1.35	
С	.079	.087	2.00	2.20	
D	.026 Nominal		0.65Nominal		
E	.047	.055	1.20	1.40	
F	.012	.016	.30	.40	
G	.000	.004	.000	.100	
Ι	.035	.039	.90	1.00	
J	.004	.010	.100	.250	
K	.012	.016	.30	.40	







#### **Micro Commercial Components**

### Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.