



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. ALBALOY PLATING (COPPER-TIN-ZINC)
  3. BERYLLIUM COPPER PER QQ-C-530
  4. GOLD PL. 50 MIN. THICK OVER COPPER PL. 100 MIN. THICK
  5. TEFLON MIL-P-19468

CONTACT PIN TO WITHSTAND 2N-cm TORQUE MINIMUM

REVISIONS					DIMENSIONS ARE IN MILLIMETERS				PART NO.		<h1>Amphenol</h1>
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE			UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE	
					0.5-6	=	±0.2			10-11-01'	
					6-30	=	±0.4			10-11-01'	
					30-120	=	±0.6			10-11-01'	
					120-315	=	±1			10-11-01'	
					315-1000	=	±1.6			10-11-01'	
					1000-2000	=	±2.4			10-11-01'	
4	RING	NOTE 1	NOTE 2	1	SMA7071A4-4B						
3	CONTACT PIN	NOTE 3	NOTE 4	1	SMA6051A1-007-3						
2	INSULATOR	NOTE 5	NATURAL	1	SMA6051A1-007-2T-50						
1	BODY	NOTE 1	NOTE 2	1	SMA6051A1-007-1						
NO	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	5/1	ISSUE	A	FILE NO.	

<b>SMA6051A1-007-N/NT50G-50</b>	
TITLE	SMA PUSH FIT JACK W/ TAB CONTACT
DRAWING NO.	
ITEM NO.	