

# AZ2250

## 30 AMP MINIATURE POWER RELAY

### FEATURES

- 1 Form A, B and C contacts available
- AC and DC coils available
- High dielectric strength version available
- Epoxy sealed versions available
- UL Class F (155°C) standard
- UL, CUR file E44211
- VDE certificate 40027037



### CONTACTS

<b>Arrangement</b>	SPST (1 Form A) SPST (1 Form B) SPDT (1 Form C)
<b>Ratings</b>	Resistive load:
<b>1 Form A</b>	Max. switched power: 840 W or 8310 VA Max. switched current: 30 A Max. switched voltage: 28 VDC or 277 VAC
<b>1 Form B</b>	Max. switched power: 280 W or 4155VA Max. switched current: 15 A Max. switched voltage: 28 VDC or 277 VAC
<b>1 Form C</b>	Max. switched power: 560 W or 8310 VA (N.O.) 280 W or 5540 VA (N.C.) Max. switched current: 30 A (N.O.) 20 A (N.C.) Max. switched voltage: 28 VDC or 277 VAC
<b>Material</b>	Silver cadmium oxide [1], silver tin oxide [2]
<b>Resistance</b>	< 50 milliohm initially (24 V, 1A voltage drop method)

### COIL

<b>Power At Pickup Voltage (typical)</b>	500 mW, DC coil 1.4 VA, AC coil
<b>Max. Continuous Dissipation</b>	1.7 W at 20°C (68°F) ambient, DC coil 2.7 VA at 20°C (68°F) ambient, AC coil
<b>Temperature Rise</b>	43°C (77°F) at nominal coil voltage
<b>Max. Temperature</b>	155°C (311°F)

### NOTES

1. All values at 20°C (68°F)
2. Relay may pull in with less than "Must Operate" value.
3. AC coils are not VDE approved
4. 18 VDC coil is not VDE approved.
5. Specification subject to change without notice.

### GENERAL DATA

<b>Life Expectancy</b> <b>Mechanical</b> <b>Electrical</b>	Minimum operations 1 x 10 <sup>7</sup> 1 x 10 <sup>5</sup> at 30 A 250 VAC
<b>Operate Time</b>	15 ms max. at nominal coil voltage
<b>Release Time</b>	10 ms max. at nominal coil voltage (with no coil suppression)
<b>Dielectric Strength (at sea level for 1 min.)</b>	2500 Vrms coil to contact 4000 Vrms coil to contact (version "T") 1500 Vrms between open contacts
<b>Insulation Resistance</b>	1000 megaohms min. at 20°C, 500 VDC 50% RH
<b>Dropout</b>	DC: > 10% of nominal coil voltage AC: > 20% of nominal coil voltage
<b>Ambient Temperature Operating</b>	-40°C (-40°F) to 85°C (185°F), DC coils -40°C (-40°F) to 70°C (158°F), AC coils
<b>Vibration</b>	1.5 mm DA at 10-55 Hz
<b>Shock</b>	10 g
<b>Enclosure</b>	P.B.T. polyester
<b>Terminals</b>	Tinned copper alloy, P.C.
<b>Max. Solder Temp.</b>	270°C (518°F)
<b>Max. Solder Time</b>	5 seconds
<b>Max. Solvent Temp.</b>	80°C (176°F)
<b>Max. Immersion Time</b>	30 seconds
<b>Weight</b>	36 grams
<b>Packing unit in pcs</b>	40 per plastic tray / 280 per carton

**ZETTLER electronics GmbH** - A ZETTLER GROUP Company

Junkersstr. 3, D-82178 Puchheim, Germany

phone: +49 89 800 97-0 office@ZETTLERelectronics.com

fax: +49 89 800 97-200 www.ZETTLERelectronics.com

This product specification to be used only together with the application notes  
which can be downloaded from <http://www.ZETTLERelectronics.com/pdfs/relais/ApplicationNotes.pdf>

2014-09-08

# AZ2250

## CONTACTS

<b>Rated load UL</b>	1 Form A 30 A at 277 VAC, General Use, 80°C, 6k cycles [1][2] 30 A at 28 VDC, resistive, 80°C, 6k cycles [1] 28 A at 277 VAC, General Use, 80°C, 100k cycles [1] 20 FLA / 60 LRA at 277 VAC, 80°C, 30k cycles [1] 2 HP at 250 VAC [1][2] 1 HP at 125 VAC [1][2]
	1 Form B 15 A at 277 VAC, General Use, 80°C, 6k cycles [1] 10 A at 28 VDC, resistive, 80°C, 6k cycles [1] 10 FLA / 33 LRA at 277 VAC, 80°C, 30k cycles [1] 0.5 HP at 250VAC [1] 0.25 HP at 125 VAC [1]
	1 Form C, (N.O.) 30 A at 277 VAC, General Use, 80°C, 6k cycles [1][2] 20 A at 277 VAC, General Use, 80°C, 6k cycles [1] 20 A at 28 VDC, resistive, 80°C, 6k cycles [1] 20 FLA / 60 LRA at 277 VAC, 80°C, 30k cycles [1] 2 HP at 250 VAC [1][2] 1 HP at 125 VAC [1][2]
	1 Form C, (N.C.) 20 A at 277 VAC, General Use, 80°C, 6k cycles [1][2] 10 A at 28 VDC, resistive, 80°C, 6k cycles [1] 10 FLA / 33 LRA at 277 VAC, 80°C, 30k cycles [1] 0.5 HP at 250 VAC [1][2] 0.25 HP at 125 VAC [1][2]

<b>Rated load VDE</b>	1 Form A, DC coils only 30 A at 250 VAC, resistive, 30k cycles [1] 15 A at 250 VAC, cos phi = 0.4, 100k cycles [1][2]
	1 Form B, DC coils only 15 A at 250 VAC, resistive, 30k cycles [1]
	1 Form C, (N.O.), DC coils only 30 A at 250 VAC, resistive, 30k cycles [1] 20 A at 250 VAC, resistive, 100k cycles [2]
	1 Form C, (N.C.), DC coils only 15 A at 250 VAC, resistive, 30k cycles [1] 10 A at 250 VAC, resistive, 100k cycles [2]
Note: 18 VDC coil is not VDE approved. AC coils are not VDE approved.	

## RELAY ORDERING DATA

COIL SPECIFICATIONS – DC Coil				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance Ohm ± 10%	1 Form A	1 Form C
5	3.75	6.5	27	AZ2250-1AT-5DF	AZ2250-1CT-5DF
6	4.5	7.8	40	AZ2250-1AT-6DF	AZ2250-1CT-6DF
9	6.75	11.7	97	AZ2250-1AT-9DF	AZ2250-1CT-9DF
12	9.0	15.6	155	AZ2250-1AT-12DF	AZ2250-1CT-12DF
15	11.25	19.5	256	AZ2250-1AT-15DF	AZ2250-1CT-15DF
18	13.5	23.4	380	AZ2250-1AT-18DF	AZ2250-1CT-18DF
24	18.0	31.2	660	AZ2250-1AT-24DF	AZ2250-1CT-24DF
48	36.0	62.4	2,560	AZ2250-1AT-48DF	AZ2250-1CT-48DF
110	82.5	143.0	13,450	AZ2250-1AT-110DF	AZ2250-1CT-110DF

COIL SPECIFICATIONS – AC Coil 50/60 Hz				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Nominal Coil Power VA	1 Form A	1 Form C
12	9.6	13.8	2.3	AZ2250-1AT-12AF	AZ2250-1CT-12AF
24	19.2	27.6	2.1	AZ2250-1AT-24AF	AZ2250-1CT-24AF
120	96.0	138.0	2.3	AZ2250-1AT-120AF	AZ2250-1CT-120AF
220	176.0	286.0	2.2	AZ2250-1AT-220AF	AZ2250-1CT-220AF
240	192.0	286.0	2.6	AZ2250-1AT-240AF	AZ2250-1CT-240AF
277	220.0	318.5	2.2	AZ2250-1AT-277AF	AZ2250-1CT-277AF

\*"1AT" or "1CT" denote silver cadmium oxide contacts.

Substitute "1BT" in place of "1AT" or "1CT" for 1 Form B relay.

Substitute "1AET" or "1CET" in place of "1AT" or "1CT" for silver tin oxide contacts.

Substitute "DEF" or "AEF" at the end of order number for epoxy sealed version.

Add "T" before "F" at the end of order number for 4000Vrms dielectric strength.

**ZETTLER electronics GmbH** - A ZETTLER GROUP Company

Junkersstr. 3, D-82178 Puchheim, Germany

phone: +49 89 800 97-0 office@ZETTLERelectronics.com


fax: +49 89 800 97-200 www.ZETTLERelectronics.com

This product specification to be used only together with the application notes which can be downloaded from <http://www.ZETTLERelectronics.com/pdfs/relais/ApplicationNotes.pdf>

2014-09-08

# AZ2250

## MECHANICAL DATA



Dimensions in inches with metric equivalents in parentheses. Tolerance:  $\pm .010$ "

**ZETTLER electronics GmbH** - A ZETTLER GROUP Company

Junkersstr. 3, D-82178 Puchheim, Germany

phone: +49 89 800 97-0 office@ZETTLERelectronics.com

fax: +49 89 800 97-200 www.ZETTLERelectronics.com

This product specification to be used only together with the application notes which can be downloaded from <http://www.ZETTLERelectronics.com/pdfs/relais/ApplicationNotes.pdf>

2014-09-08