
KEMET Part Number: C927U222MYWDBA7317



Ceramic, Safety, C900_Y, 2200 pF, 20%, Y5U, Lead Spacing = 7.5mm



| Dimensions | |
|------------|-----------------|
| D | 9mm MAX |
| Т | 5mm MAX |
| S | 7.5mm +/-1mm |
| LL | 18mm +2/-0mm |
| F | 0.55mm +/-0.1mm |

| Packaging Specifications | | |
|--------------------------|--|--|
| Packaging: | Ammo, H0 = 18mm, Component Pitch = 15mm | |
| Packaging Quantity: | 1000 | |

| General Information | | |
|---------------------|-------------|--|
| Style: | Radial Disc | |
| Series: | C900_Y | |
| RoHS: | Yes | |
| Termination: | Tin | |
| Failure Rate: | N/A | |
| Halogen Free: | Yes | |

| Specifications | | |
|--------------------------|-----------|--|
| Capacitance: | 2200 pF | |
| Capacitance Tolerance: | 20% | |
| Temperature Range: | -40/+125C | |
| Temperature Coefficient: | Y5U | |
| Dissipation Factor: | 2.5% | |
| Insulation Resistance: | 10 GOhms | |
| Dielectric Strength: | 2,600 V | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

